

BRAND NEW & VERIFIED



VERIFIED PRODUCT DATASHEET

C9115AXI-E

Cisco Network Hardware Specification, Availability and Quote Reference

Product Model	C9115AXI-E
Document Type	Product Datasheet
Condition	Brand New, Original and Verifieded
Supplier	Layer23-Switch.com

200+ Countries Sold	18,000+ Customers Trusted	\$20M Inventory Available	1-Year Warranty Support
-------------------------------	-------------------------------------	-------------------------------------	-----------------------------------

Need Price or Availability?

View product details, check stock, or request a fast quotation from Layer23-Switch.

[View Product Page & Request a Quote](#)

C9115AXI-E Datasheet

The Cisco C9115AXI-E datasheet provides verified specifications, key features, and application scenarios. This document helps engineers and IT buyers quickly evaluate the C9115AXI-E and integrate it into enterprise or service provider networks with confidence.

[Read More](#) | [Quote](#)



Specification

Category	Parameter	Specification	Notes
Product	Model	C9115AXI-E (Catalyst 9115AXI, regulatory domain E)	Verify local regulatory approval
Architecture	Deployment	Controller-based (CAPWAP)	AireOS 8.9+; IOS-XE 16.11+ on controllers
Radios	Spatial streams	4x4:4 (2.4GHz); 4x4:4 (5GHz)	Simultaneous dual-band
Wi-Fi features	802.11ax (incl.)	OFDMA (UL/DL), MU-MIMO, TWT, BSS Coloring, beamforming, MRC	
Throughput	Max PHY rate	Up to 5.38Gbps	160MHz@5GHz + 20MHz@2.4GHz
Antennas	Integrated gain	2.4GHz 3dBi; 5GHz 4dBi	Omnidirectional in azimuth
Interfaces	Ethernet uplink	1x 100/1000/2500 Base-T (mGig, 802.3bz)	Cat5e supports all speeds
Interfaces	Console	RJ-45 (management console)	
Interfaces	USB	USB 2.0	

Category	Parameter	Specification	Notes
IoT	Bluetooth	Integrated Bluetooth 5.0	
Power	Input types	802.3at PoE+, 802.3bt UPOE(+), 802.3af	Injectors: AIR-PWRINJ6= (at), AIR-PWRINJ5= (af)
Power	PoE behavior	802.3at: 4x4 radios, 2.5G link, USB on	Max PoE consumption 20.4W (AXI)
Power	Reduced feature mode	When 802.3af: 2x2 radios, 1G link, USB off	Enable LLDP/CDP for proper power negotiation
Environmental	Operating temperature	0-50°C (32-122°F)	When >40°C: 4x4→2x2; uplink 1G; USB off
Environmental	Operating humidity	10%-90% (non-condensing)	
Environmental	Storage temperature	-30-70°C (-22-158°F)	
Environmental	Operating altitude test	9843ft (3000m) @ 40°C	
Memory	System memory	2048MB DRAM; 1024MB flash	
Physical	Dimensions (WxLxH)	8.0x8.0x1.5in (20.3x20.3x3.8cm)	AP only (no bracket)
Physical	Weight	1.98lb (0.9kg)	AP only
Compliance	Safety/EMC/Radio	Meets IEC/EN/UL 60950-1, 62368-1, CISPR/EN 55032/24/35, EN 300 328, EN 301 893, FCC Part 15, etc.	See datasheet compliance list
Security	WLAN security	WPA3/WPA2/WPA; 802.1X; AES; EAP-TLS/TTLS/PEAP/EAP-FAST/SIM, etc.	
Controllers	Supported platforms	Catalyst 9800 Series; 3504; 5520; 8540; vWLC	Minimum versions as above

Want to Buy

[Order Now](#) [Get a Quote](#)

Why Layer23-Switch.com

As a leading network hardware supplier, Layer23-Switch.com focuses on original new ICT equipment of Cisco, H3C, Juniper, etc.

200+

Countries we Sold

18,000+

Customers Trusted

\$20,000,000

Inventory Available

50%-98%

Off Global List Price

100%

Safe Online Shopping

Contact Us

- WhatsApp: [+8617181189993](https://wa.me/8617181189993)
- Wechat: [layer23-switch](#)
- Telegram: [layer23_switch](#)
- Email: sales@layer23-switch.com

Need Price and Availability for C9115AXI-E?

View product details, request a quote, or check current stock from Layer23-Switch.

[View Product Details & Request a Quote](#)