



C9300L-24T-4X-E DataSheet

Cisco C9300L-24T-4X-E—24 × 1 Gb data ports with 4 × 10 Gb SFP+ uplinks, 128 Gbps fabric, StackWise-320, Network Essentials for scalable campus and branch access.

READ MORE



C9300L-24T-4X-E Description



The C9300L-24T-4X-E delivers 24 1 Gb RJ-45 ports and four built-in 10 Gb/1 Gb SFP+ uplinks over a 128 Gbps non-blocking fabric. StackWise-320 allows up to eight switches to form a single logical unit with 320 Gbps per switch and < 50 ms fail-over. Network Essentials provides Layer 3 static routing, VLAN segmentation, QoS, and DNA Center automation. A single 350 W AC power supply runs all data-only functions; an optional second PSU adds redundancy. With 8 GB DRAM, 16 GB flash, and an optional USB 3.0 SSD slot, it supports on-box container apps for telemetry and security.

Quick Specs

C9300L-24T-4X-E	Specification
Switching capacity	128 Gbps non-blocking; 448 Gbps (stacked)
Forwarding rate	95.23 Mpps; 333.33 Mpps (stacked)
Packet buffer size	16 MB shared buffer
Downlink ports	24 × 10/100/1000 Mb RJ-45 (non-PoE)

Uplink ports	4 × 1/10 Gb SFP+ fixed uplinks
Stacking	StackWise-320: 320 Gbps per switch; up to 8 members; < 50 ms fail-over
Default PSU / Power budget	350 W AC (no PoE)
DRAM / Flash	8 GB / 16 GB
Software license	Network Essentials (-E)

Key Features


Product Comparison

Parameter	C9300L-24T-4X-E	C9300L-24P-4X-E	C9300L-24T-4G-E
Switching capacity	128 Gbps (448 Gbps stacked)	128 Gbps (448 Gbps stacked)	56 Gbps (376 Gbps stacked)
Forwarding rate	95.23 Mpps (333.33 Mpps)	95.23 Mpps (333.33 Mpps)	41.66 Mpps (279.76 Mpps)
Packet buffer size	16 MB	16 MB	16 MB
Downlink interfaces	24 × 1 Gb (non-PoE)	24 × 1 Gb PoE+ (30 W)	24 × 1 Gb (non-PoE)
Uplink ports	4 × 10 Gb/1 Gb SFP+	4 × 10 Gb/1 Gb SFP+	4 × 1 Gb SFP
Default PSU	350 W AC	715 W AC (445 W PoE)	350 W AC
Software license	Network Essentials (-E)	Network Essentials (-E)	Network Essentials (-E)

C9300L-24T-4X-E Switch Rear Panel

The switch rear panel includes StackWise connectors, StackPower or XPS connectors, ports, fan modules, and power supply modules.

1	Ground connectors	7	StackPower connectors
2	USB3.0-SSD port	8	AC OK (input) status LED
3	BEACON LED	9	PS OK (output) status LED
4	CONSOLE (RJ-45 console port)	10	StackWise-480 port connectors
5	MGMT (RJ-45 10/100/1000 management port)	11	Power supply modules
6	Fan modules	-	-




Components Delivered in the Shipping Box

The shipping box contains the model of the switch you ordered and other components needed for installation. Some components are optional, depending on your order.

1	Cisco Catalyst 9300 Series switch with optional network module ¹ (power supply and fan modules not shown)	9	Eight number-8 Phillips flat-head screws
2	AC power cord	10	Cable guide

3	Product documentation and compliance document	11	M4.0 x 20mm Phillips pan-head screw
4	Four rubber mounting feet	12	(Optional) RJ-45 console cable
5	Ground lug screw and ring terminal	13	(Optional) USB console cable
6	Two 19-inch mounting brackets	14	(Optional) StackWise-480/1T cable (0.5-meter, 1-meter, or 3-meter)
7	Four number-12 pan-head screws	15	(Optional) StackPower cable (0.3-meter or 1.5-meter)
8	Four number-10 pan-head screws	16	(Optional) StackWise-320 cable



Specification

Cisco Catalyst C9300L-24T-4X-E Detailed Specifications

Model SKU	C9300L-24T-4X-E
Software Image	Network Essentials (-E)
Switching Capacity	128 Gbps (non-blocking)

Cisco Catalyst C9300L-24T-4X-E Detailed Specifications

Forwarding Rate	95.23 Mpps (64-byte IPv4)
Stacking Bandwidth	320 Gbps per switch; 448 Gbps end-to-end
Max Stack Members	8
Downlink Interfaces	24 × RJ-45 10/100/1000 Mb (non-PoE)
Uplink Ports	4 × 10 Gb/1 Gb SFP+ fixed uplinks
Packet Buffer	16 MB shared buffer
DRAM / Flash	8 GB / 16 GB
IPv4 Routes (total)	16 000
IPv6 Routes (total)	16 000
ACL Entries	5 120
QoS Entries	5 120
VLAN IDs	4 094
MAC Address Table	32 000 entries
External SSD	Optional USB 3.0 SSD slot (up to 240 GB)
Fans	3 × field-replaceable, N+1 redundant
Default PSU	350 W AC (no PoE)
Dimensions (H × W × D)	1.73 × 17.5 × 16.1 in (4.4 × 44.5 × 40.9 cm)
Weight (with PSU)	14.99 lb / 6.81 kg
Operating Temperature	-5 °C to +45 °C (sea level)
Security Features	Secure Boot, Trust Anchor SUDI, MACsec AES-256
App Hosting	Container support (ThousandEyes, ASA-C)
SD-Access	Group-based policy, on-box automation, fabric segmentation

Want to Buy

[ORDER NOW](#) [GET A QUOTE](#)

Why Layer23-Switch.com

As a leading network hardware supplier, Layer23-Switch.com focuses on original new ICT equipment of Cisco, H3C, Juniper, etc.

200+

Countries we Sold

18,000+

Customers Trusted

\$20,000,000

Inventory Available

50%-98%

Off Global List Price

100%

Safe Online Shopping

Contact Us

- WhatsApp: [+8617181189993](https://wa.me/8617181189993)
- Wechat: [17181189993](https://www.wechat.com/qrcode/business?business_id=17181189993)
- Email: sales@layer23-switch.com