Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-BAR-W-C-K9

Carbon Finish · Wall-Mount Navigator · Cisco Room Bar

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	**CS-BAR-W-C-K9**
Category	**Cisco Video Conferencing**
Condition	**New, factory-sealed**
Warranty	**3-year LSCare warranty**
Supplier	**Layer23-Switch** · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty



CISCO VIDEO CONFERENCING

CS-BAR-W-C-K9

Carbon Finish · Wall-Mount Navigator · Cisco Room Bar

The CS-BAR-W-C-K9 is a Cisco Room Bar all-in-one video bar for huddle spaces and small meeting rooms, supplied in Carbon with a wall-mount Room Navigator. The bar has a 12MP camera with a 120-degree horizontal field of view, a 4-element beamforming microphone array, stereo speakers rated to 93 dB and two HDMI outputs at 3840 x 2160 at 60 fps.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-BAR-W-C-K9	**Cisco ordering description**	Cisco Room Bar in Carbon colour with wall-mount Room Navigator
Published room coverage	Optimized for huddle and small meeting rooms with up to 5 people within 3 metres; rooms above 5 people need external microphones, and speaker tracking assumes the furthest participant is within 3 metres	**Network interface**	One Ethernet RJ-45 at 100/1000 Mbps for LAN
Controller port	One Ethernet RJ-45 at 100/1000 Mbps with PoE, dedicated to direct pairing of the Cisco Room Navigator	**Other interfaces**	Bluetooth and Bluetooth Low Energy, one USB 2.0 type A, one micro-USB service port and a factory reset pinhole
Camera	12 MP on a 1/2.3 in CMOS sensor at 30 fps	**Camera lens**	Fixed focus at f/2.5 aperture
Camera field of view	120 degrees horizontal and 95 degrees vertical	**Camera zoom**	5x digital zoom
Camera intelligence	Auto framing with face detection, speaker tracking, automatic brightness and white balance, automatic image rotation when inverted, Frames mode for single-person framing	**Video standards**	H.263, H.264 and AV1
Video input	One HDMI up to 3840 x 2160 at 30 fps including 1920 x 1080 at 60 fps, and one USB-C up to 3840 x 2160 at 30 fps, both with CEC 2.0	**Video outputs**	Two HDMI up to 3840 x 2160 at 60 fps with CEC 2.0, supporting touch screens when a USB-A touch signal is attached
Live video resolutions	Encode and decode up to 1920 x 1080 at 30 fps and 60 fps	**Video stream**	1920 x 1080 at 30 fps
Content stream	3840 x 2160 at 15 fps, with 3840 x 2160 at 15 fps content decode from Webex	**Audio standards**	G.711, G.722, G.722.1, G.729, AAC-LD and Opus
Audio features	Acoustic echo cancellation, active lip sync, AI noise removal, automatic gain control, beamforming microphone, dereverberation, full duplex, full-band audio, Self-Hear, spatial audio and ultrasound	**Loudspeaker system**	Stereo pair of two full-range drivers with directional audio
Loudspeaker response	100 Hz to 20 kHz within plus or minus 3 dB at 93 dB maximum sound pressure level	**Microphone array**	4-element beamforming array with an additional front-facing microphone for speaker tracking

LAYER23-SWITCH

Audio inputs	One HDMI, one analogue microphone input, one DisplayPort over USB-C, one USB-A, Bluetooth, and one PoE port carrying audio over IP for a single Cisco IP microphone	**Audio outputs**	One DisplayPort over USB-C, one USB-A and Bluetooth
Wireless	Wi-Fi 802.11a/b/g/n/ac on 2.4 and 5 GHz with 2x2 MIMO	**Accessory part number**	PSU-12VDC-86W= power supply spare
USB-C passthrough	Camera, microphone and speakers over one USB-C cable with simultaneous content sharing and 3840 x 2160 at 30 fps display extension, requiring Alt-mode DisplayPort on the computer	**Software compatibility**	RoomOS 11 or later for native Webex meetings with interoperability for Microsoft Teams, Zoom and Google Meet
Power input	100 to 240 VAC at 50/60 Hz with 12V DC input, requiring the PSU-12VDC-86W power supply	**Maximum power consumption**	86W peak, 14.3W in call, 8.2W idle and 7W networked standby
Dimensions	21 x 3.2 x 2.5 in (53.4 x 8.2 x 6.4 cm)	**Mounting**	Consolidated mounting unit for walls and screens with a gap bar closing the seam, mounted above or beneath the screen and invertible for cable routing with a de-attachable flipped speaker grille
Operating temperature	0 to 35°C at 10% to 90% relative humidity	**Compliance model number**	TTC7-28

Get Price and Availability for CS-BAR-W-C-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.