CISCO VIDEO CONFERENCING

CS-DESK-K9

24-Inch 1080p Touch Display · USB-C Passthrough · Cisco Desk

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CS-DESK-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty



CISCO VIDEO CONFERENCING

CS-DESK-K9

24-Inch 1080p Touch Display · USB-C Passthrough · Cisco Desk

The CS-DESK-K9 is a Cisco Desk personal video endpoint for individual desks, where it replaces both the monitor and the webcam. The endpoint has a 24-inch 1080p touch display, an 8 MP camera with a 64-degree horizontal field of view, a four-microphone array and a 70W maximum rated power draw.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-DESK-K9	**Cisco ordering description**	Cisco Desk (First Light) - Upfront GPL
User interface	Projected capacitive multi-touch	**Supported PC resolutions**	1080p60
Camera optics	64 degrees horizontal and 50 degrees vertical field of view at f/2.0 aperture, focusing from 10 cm to infinity	**Multipoint support**	Four-way embedded SIP and H.323 conferencing capability with the MultiSite option
Peripherals supported	USB headset and wideband Bluetooth headset	**Display**	24-inch LCD monitor at 1080p resolution in 16:9, on a high-contrast VA LED panel
Display characteristics	Contrast ratio 1000:1 typical, viewing angle plus or minus 89 degrees typical, brightness 300 cd/m2, colour depth 16.7M colours and colour gamut 72% NTSC or 95% sRGB	**Camera sensor**	8 MP image sensor on a 1/3.2-inch CMOS supporting up to 30 fps
Camera intelligence	Automatic tilt adjustment with automatic focus, brightness and white balance	**Camera privacy**	Privacy shutter with LED light
Video standards	H.263 and H.264 AVC	**Video inputs**	USB-C DisplayPort Alternate Mode up to 1920 x 1080p60 and one HDMI 2.0 type A input up to 1920 x 1080p60
Video stream	Full HD 1080p30	**Content stream**	1080p60, with up to 4K content decode from Webex
Audio standards	G.711, G.722, G.722.1, G.729, AAC-LD and Opus	**Audio features**	High-quality full-band audio, automatic gain control, AI-powered noise removal, active lip synchronization, focused microphone pickup and music mode
Audio inputs	Dynamic four-microphone array, audio in from HDMI, audio in from DisplayPort over USB-C, USB and Bluetooth	**Audio outputs**	External USB headset and Bluetooth headset
Loudspeaker	Premium full-range centre speaker with passive bass radiators for extended low-frequency output, covering 80 Hz to 20 kHz	**MultiSite capability**	Three-way at up to 1080p30 with content up to 1080p15, four-way at up to 720p30 with content up to 1080p15, full individual audio and video transcoding, mixed H.323, SIP and VoIP in one conference, and H.239 or BFCP presentation from any participant up to 3840 x 2160p5
Network standby staging	Halfwake after 2 minutes idle, DisplayOff standby after 10 minutes and networked standby after 12 minutes	**Sensors**	Temperature and humidity, both marked experimental, reported for Control Hub analytics

LAYER23 SWITCH

Default components	Cisco Desk, Desk Stand, 3 m network cable, 1.8 m USB-C cable for USB passthrough and the power supply	**Optional hardware components**	Replaceable metal speaker grille, stylus kit and wall mount
Packaged size	72.4 x 20 x 69.5 cm (28.5 x 7.9 x 27.4 in)	**Locking mechanism**	Kensington security lock
Wireless sharing	Webex App and Webex Meetings	**Embedded encryption**	Webex end-to-end encryption, H.323 and SIP point-to-point, standards-based H.235 v3 and AES, with automatic key generation and exchange
Ordering variants	CS-DESK-C-K9 Carbon Black, CS-DESK-NR-K9 no radio, CS-DESK-K9++ TAA, CS-DESK-NR-K9++ no radio TAA, CS-DESK-NR-K7 no radio and no encryption, CS-DESK-MM-K9 and CS-DESK-MM-NR-K9 made in Mexico	**Accessory part numbers**	CAB-ETH-3M-GR= 3 metre grey Ethernet cable and CS-DESK-STYLUSKIT= stylus kit with 2 styluses and 4 tips
Regulatory approvals	Directive 2014/53/EU for radio versions, Directives 2014/30/EU and 2014/35/EU for non-radio versions, Directive 2011/65/EU, Directive 2002/96/EU, NRTL approval, FCC CFR 47 Part 15B Class B, Part 15C and FCC Listed	**USB-C BYOD**	Display extension at 1920 x 1080 at 60 fps requiring Alt-mode DisplayPort on the computer, touch redirect on supported operating systems, and use of the desk camera, microphone and speakers with any software client
Other USB ports	One standard USB 2.0 type-A port for headsets and handset use, and one Micro B USB port for service only	**Software compatibility**	RoomOS 11 or later
Software option	LIC-DESK-MS MultiSite	**Power**	70W maximum rated with networked standby consumption at 7.5W maximum
Dimensions	Width 56.5 cm (22.2 in), height 47.4 cm (18.7 in) and depth 7.0 cm (2.8 in)	**Operating temperature**	0°C to 35°C (32°F to 104°F) ambient
Storage temperature	-20°C to 60°C (-4°F to 140°F)	**Operating humidity**	20% to 90% relative humidity
Storage humidity	10% to 90% relative humidity, noncondensing	**Compliance model number**	TTC7-30

Get Price and Availability for CS-DESK-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.