Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-KIT-EQ-4K-K9

20x Optical PTZ Camera · Codec EQ With Four PoE++ Ports · Cisco Room Kit EQ

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	**CS-KIT-EQ-4K-K9**
Category	**Cisco Video Conferencing**
Condition	**New, factory-sealed**
Warranty	**3-year LSCare warranty**
Supplier	**Layer23-Switch** · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty



CISCO VIDEO CONFERENCING

CS-KIT-EQ-4K-K9

20x Optical PTZ Camera · Codec EQ With Four PoE++ Ports · Cisco Room Kit EQ

The CS-KIT-EQ-4K-K9 is a Cisco Room Kit EQ PTZ 4K collaboration bundle for large rooms where the camera has to reach distant seats. The Cisco PTZ 4K Camera zooms 20x optically and 240x in total, pans plus or minus 170 degrees and tilts from -20 to +90 degrees, while the Codec EQ drives three HDMI displays at 3840 x 2160 at 60 fps.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-KIT-EQ-4K-K9	**Cisco ordering description**	Cisco Room Kit EQ PTZ 4K with Cisco Codec EQ, Cisco PTZ 4K Camera and Cisco Room Navigator for Table (First Light)
Bandwidth	Up to 20 Mbps, with minimums of 768 kbps for 720p30, 1152 kbps for 720p60, 1472 kbps for 1080p30 and 2560 kbps for 1080p60	**Bundle components**	CS-CODEC-EQ-K9+, CS-CAM-PTZ4K+ and CS-T10-TS-L+
Camera resolution	1920 x 1080 at 60 fps and 3840 x 2160 at 30 fps	**Camera zoom**	240x total, from a 20x optical stage and 12x digital zoom
Camera pan range	Plus or minus 170 degrees, used for manual control and presets	**Camera tilt range**	-20 degrees to +90 degrees, used for manual control and presets
Camera field of view	70 degrees horizontal	**Camera f-value**	2.0 to 3.8, focusing from 1.0 m to infinity at the wide end
Camera control	Visca over IP on the LAN port, with video over HDMI 2.0	**Presenter tracking**	PresenterTrack with digital cropping
Video inputs	One USB-C up to 3840 x 2160 at 30 fps on USB 3.2 gen1 at up to 5 Gbps, three HDMI up to 3840 x 2160 at 30 fps including 1920 x 1080 at 60 fps with HDCP 1.4 on one input, and four PoE++ 1 Gb Ethernet ports carrying up to three 1920 x 1080 at 60 fps video-over-IP streams or one 3840 x 2160 at 30 fps stream, with EDID and CEC 2.0	**Video outputs**	Three HDMI up to 3840 x 2160 at 60 fps with CEC 2.0 and interactive touch screen connectivity via HDMI out and USB-A
Main video	1920 x 1080 at 60 fps	**Presentation channel**	3840 x 2160 at 15 fps
Video standards	H.264, H.265, H.263 and AV1	**Firewall traversal**	Cisco Expressway technology with H.460.18 and H.460.19
Audio standards	G.711, G.722, G.722.1, G.729, AAC-LD and Opus	**Audio features**	High-quality 20 kHz full-band audio, prepared for inductive loop on line out, acoustic echo cancellation, active lip synchronization, AI-powered adaptive noise removal, automatic gain control, full duplex, Self-Hear and ultrasound technology

LAYER23 SWITCH

Audio inputs	Three mini-jack analogue inputs, three HDMI inputs, one USB-C, one USB-A, four PoE++ Ethernet for audio over IP, connectivity with up to eight Cisco IP microphones, and third-party audio systems over AES67 with the AV Integrator License	**Audio outputs**	One analogue line out, three HDMI audio outputs, one USB-A, one USB-C and four PoE++ Ethernet
Locking mechanism	Kensington security lock on the Codec EQ	**Codec spare parts**	CS-CODEC-EQ-RCK= rack ears, CS-CODEC-EQ-WMK= wall-mount kit and CS-CODEC-EQ-ANT= antennas
Bundle variants	CS-KIT-EQ-4K-NRK9 non-radio and CS-KIT-EQ-4K-K9++ TAA, both retaining the PTZ 4K Camera and table-stand Room Navigator	**USB passthrough**	One USB 3.2 gen1 at up to 5 Gbps providing camera, microphone and speakers over a single USB-C cable with simultaneous content sharing and 3840 x 2160 at 30 fps display extension, requiring Alt-mode DisplayPort on the computer
Software options ordered separately	L-ROOM-RM remote monitoring, L-KITEQ-MS embedded MultiSite and L-KITEQ-AV AV integrator pack	**Camera power**	12V at 3A from 100 to 120 or 200 to 240 VAC at 50/60 Hz, or PoE+ compatible with IEEE 802.3at, using FSP040-RHAN3, Phihong POE29U-1AT(PL) or Microsemi PD-9001GR/AT/AC
USB-C power output	15W maximum	**Dimensions**	Codec: 18.6 x 1.7 x 8 in (47.3 x 4.4 x 20.2 cm)
Camera mounting	Wall mount or upside-down ceiling mount, using CS-PTZ4K-BRKT or CS-PTZ4K-CLNGMNT	**Operating temperature**	Codec EQ and Room Navigator 0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)	**Operating humidity**	10% to 90% relative humidity
Storage humidity	10% to 90% relative humidity, noncondensing	**Compliance model numbers**	TTC6-15 for the Codec EQ, EVI-X200C for the PTZ 4K Camera and TTC5-15 for the Room Navigator

Get Price and Availability for CS-KIT-EQ-4K-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.