Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-KITPLPTZ4K-K9

20x Optical PTZ Camera · Codec Plus With Three Gigabit Ports · Cisco Room Kit Plus

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	**CS-KITPLPTZ4K-K9**
Category	**Cisco Video Conferencing**
Condition	**New, factory-sealed**
Warranty	**3-year LSCare warranty**
Supplier	**Layer23-Switch** · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty



CISCO VIDEO CONFERENCING

CS-KITPLPTZ4K-K9

20x Optical PTZ Camera · Codec Plus With Three Gigabit Ports · Cisco Room Kit Plus

The CS-KITPLPTZ4K-K9 is a Cisco Room Kit Plus PTZ 4K integrator bundle for meeting rooms built around one pan-tilt-zoom camera. The Codec Plus provides three gigabit Ethernet ports, two HDMI outputs at 3840 x 2160 and 60 fps and up to 6 Mbps point to point, and the camera adds 240x total zoom.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-KITPLPTZ4K-K9	**Cisco ordering description**	Webex Room Kit Plus PTZ 4K - bundle SKU
Network interfaces	One Ethernet RJ-45 at 10/100/1000 for LAN, one Ethernet RJ-45 at 10/100/1000 for direct pairing with the camera for camera control, and one Ethernet RJ-45 at 10/100/1000 with PoE dedicated to direct pairing with the Webex Room Navigator	**Other interfaces**	One USB A port, USB-B, micro USB and a factory reset pinhole
Camera optics	f/2.0 to f/3.8, focusing from 1.0 m to infinity at the wide end, with focus, white balance and brightness selectable as manual or automatic	**Bandwidth**	Up to 6 Mbps point to point, with H.264 minimums of 768 kbps for 720p30, 1152 kbps for 720p60, 1472 kbps for 1080p30 and 2560 kbps for 1080p60
Bundle components	Webex Codec Plus as CS-CODEC-PLUS+, Webex PTZ 4K Camera as CS-CAM-PTZ4K+ and Webex Room Navigator control unit as CS-T10-TS+	**Firewall traversal**	Cisco Expressway technology with H.460.18 and H.460.19
Video standards	H.264 and H.265, with H.263 for TANDBERG MXP interoperability only	**Video inputs**	One HDMI input up to 1080p60 and two HDMI inputs up to 4K (3840 x 2160) at 30 fps including 1080p60, with EDID and CEC 2.0
Video outputs	Two HDMI outputs up to 3840 x 2160 at 60 fps with CEC 2.0	**Main video**	Full HD 1080p60
Presentation channel	UHD 4K 2160p5, including 1080p30 and 720p60	**Audio standards**	G.711, G.722, G.722.1, G.729, AAC-LD and Opus
Audio features	High-quality 20 kHz audio, prepared for inductive loop on line out, automatic gain control, automatic noise reduction and active lip synchronization	**Audio inputs**	Three microphone inputs on 4-pin mini-jack, plus embedded audio on two HDMI inputs
Audio outputs	One stereo line out mini-jack on the Codec Plus, embedded audio on one HDMI output, and Audio Return Channel support on HDMI input one	**PresenterTrack**	Intelligent face and upper-body detection and tracking, configured on the Codec Plus system for a defined stage area; once the presenter enters the trigger zone the pan-tilt-zoom camera follows with best overview, framing and zoom level while they move inside the defined stage area

LAYER23-SWITCH

Alternative camera pairing	Compatible with the Webex SpeakerTrack 60 Camera and the Webex Quad Camera bar for intelligent framing and speaker tracking	**Wireless**	Wi-Fi 802.11a/b/g/n/ac on 2.4 GHz and 5 GHz with 2x2 MIMO; 802.11d must be enabled on the access point for operation between 5725 MHz and 5875 MHz, and Ethernet is preferred for high performance
Camera resolution	1920 x 1080 at 60 fps and 3840 x 2160 at 30 fps	**Camera zoom**	240x total, from a 20x optical stage and 12x digital zoom
Camera pan range	Plus or minus 170 degrees	**Camera tilt range**	-20 degrees to +90 degrees
Camera field of view	70 degrees horizontal	**Camera control**	Visca over IP on the LAN port
Locking mechanism	Kensington security lock	**Security**	X.509 digital certificates in DER encoded binary, with DER and Base-64 formats accepted for client and server certificates and key sizes of 1024, 2048 and 4096 supported
Optional hardware components	Cisco Table Microphone, Cisco Ceiling Microphone, wall mount for the Codec Plus and assorted cables	**Hardware options ordered separately**	PSU-12VDC-40W2= camera power supply, CS-PTZ4K-BRKT= camera wall mount bracket and AIR-PWRINJ6 power injector
Spare part numbers	CS-CODEC-PLUS= for the Codec Plus and CS-CAM-PTZ4K= for the PTZ 4K Camera	**Regulatory approvals**	Directive 2011/65/EU, Directive 2002/96/EU, NRTL approval, FCC Listed for radio equipment, radio standards EN 300 328, EN 301 893 and EN 300 440, EMC standards EN 301 489-1 and -17, EN 55032 Class A and EN 55024, safety standards EN 60950-1, EN 62479 and EN 62311, and FCC CFR 47 Part 15B Class A, Part 15C and Part 15E
Software compatibility	Cisco Collaboration Endpoint (CE) Software Version 9.14.5 or later, or Cisco Webex RoomOS	**Software options ordered separately**	L-KIT-RM remote monitoring and L-KITPLUS-MS embedded MultiSite
Power supply	100 to 240 VAC at 50/60 Hz with 12V DC input, averaging 20 W at a 70 W peak	**Dimensions**	Codec dimensions: 14.1 x 1.7 x 5.6 in (35.9 x 4.3 x 14.3 cm)Camera dimensions: 6.3 in wide by 7.0 in high at maximum tilt by 8.0 in deep (15.8 x 17.7 x 20.0 cm)
Operating temperature	0°C to 35°C (32°F to 95°F) ambient	**Storage temperature**	-20°C to 60°C (-4°F to 140°F)
Operating humidity	10% to 90% relative humidity	**Storage humidity**	10% to 90% relative humidity, noncondensing
Component compliance models	TTC7-25 for the Codec Plus, EVI-X200C for the PTZ 4K Camera and TTC5-15 for the Room Navigator; Cisco publishes no compliance model for the bundle SKU		

LAYER23-SWITCH

Get Price and Availability for CS-KITPLPTZ4K-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH