Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-MIC-TABLE-J

4-Pin Mini Jack · 7.5 m Cable · Cisco Table Microphone

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	**CS-MIC-TABLE-J**
Category	**Cisco Video Conferencing**
Condition	**New, factory-sealed**
Warranty	**3-year LSCare warranty**
Supplier	**Layer23-Switch** · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty



CISCO VIDEO CONFERENCING

CS-MIC-TABLE-J

4-Pin Mini Jack · 7.5 m Cable · Cisco Table Microphone

The CS-MIC-TABLE-J is a Cisco Table Microphone, a balanced omnidirectional boundary-layer microphone for fixed-table meeting rooms that connect through a codec audio input. The microphone covers 80 Hz to 20 kHz with -34 dB free-field sensitivity and a 1.5 m pickup radius over 360 degrees, on a 7.5 m cable with a 4-pin mini jack.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-MIC-TABLE-J	**Cisco ordering description**	Cisco Table Microphone with 4-pin mini jack connector, 7.5 meters cable, ordered as CS-MIC-TABLE-J=
Product compatibility	Room Bar, Room Bar Pro, Room Kit, Room Kit Plus, Room Kit EQ, Room Kit EQX, Room Kit Pro, Room 55, Room 55 Dual, Room 70, Room 70 G2, SX10, SX20, SX80, MX700, MX800, Board Pro 55/75, Board Pro 55/75 G2 and the Room Panorama Series	**Connector type**	4-pin mini jack, with a 4-pin Euroblock version available separately as CS-MIC-TABLE-E=
Speaker tracking support	Not supported on this model	**Description**	Balanced omnidirectional table microphone, boundary layer type
Cable length	7.5 metres	**Free field sensitivity**	-34 dB plus or minus 3 dB rel 1V/Pa at 1 kHz
Pickup range	1.5 m radius with 360-degree coverage	**Mute functionality**	LED showing mute status with a mute and unmute button on the device
Colour	White	**Adaptive voice capture**	Not supported on this model
Scalability via switch	Not supported; the microphone connects to a codec audio input rather than an Ethernet network	**Automatic positioning**	Not supported on this model
Audio encryption	AES-128 audio encryption is not supported on this model	**Extension cable**	CAB-MIC-EXT-J= adds 9 metres for 4-pin mini jack cables
Spare part numbers	CAB-MIC-TABLE-J= spare cable for the 4-pin mini jack connector and CS-MIC-TABLE-PLA= spare table-top metal plate in packs of three	**Cloud device management**	Not supported on this model
Frequency range	80 Hz to 20 kHz, plus or minus 6 dB	**Phantom power**	9V or 52V
Signal-to-noise ratio	Minimum 70 dB	**Dimensions**	Round shape at 6.39 cm diameter by 1.09 cm (2.52 in diameter by 0.43 in)
Mounting	Tabletop, either recessed into the table or placed on a magnetic table plate		

LAYER23-SWITCH

Get Price and Availability for CS-MIC-TABLE-J

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH