Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-T10-TS-L-K9

10.1-Inch Table Controller · 180-Degree Rotating UI · Cisco Room Navigator


New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	**CS-T10-TS-L-K9**
Category	**Cisco Video Conferencing**
Condition	**New, factory-sealed**
Warranty	**3-year LSCare warranty**
Supplier	**Layer23-Switch** · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty



CISCO VIDEO CONFERENCING

CS-T10-TS-L-K9

10.1-Inch Table Controller · 180-Degree Rotating UI · Cisco Room Navigator

The CS-T10-TS-L-K9 is a Cisco Room Navigator touch controller on a table stand for meeting tables that run Cisco Room, Board or Desk video devices. The panel has a 10.1-inch capacitive touch display at 1920 x 1200, 4 GB of memory, one 100 Mbps Ethernet RJ-45 port and 802.3af Class 0 PoE.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-T10-TS-L-K9	**Cisco ordering description**	Cisco Room Navigator - Table-Stand (First Light)
Product compatibility	Cisco Room Series, Cisco Board Series including Board S Series, Board Pro and Board Pro G2 Series, and Cisco Desk Series	**Call control compatibility**	Hosted deployments controlled by the codec, Cisco Unified Communications Manager 10.5.2 or newer and Webex Cloud; cloud deployments on Webex Cloud
Interface orientation	The table version of the user interface rotates 180 degrees when the device is tilted, allowing two viewing angles	**Interfaces**	One Ethernet RJ-45 at 100 Mbps for LAN or direct pairing, one microUSB service port and one factory reset pinhole
Language support	English, Arabic, Catalan, Czech, Danish, Dutch, Finnish, French, German, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazilian, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish and Ukrainian	**Memory**	4 GB
Default components	Room Navigator touch panel and table stand in First Light	**Display**	Capacitive touch LCD at 10.1-inch diagonal with anti-glare and anti-fingerprint finish
Resolution	1920 x 1200	**Cisco scheduler**	Integrates with O365, Exchange and Google Calendar through the Webex Hybrid Calendar service, with ad-hoc or ahead reservation, room calendar view, check-in, auto ghost meeting release, meeting extension and touchless booking with Cisco AI Assistant
Third-party web applications	Persistent web applications for room booking, wayfinding and digital signage, with access to room sensor data and the Webex hybrid calendar	**In-room controls**	Administrator-configurable control of lighting, blinds, room dividers and curtains
Sensors	Temperature, relative humidity and air quality (TVOC), combined with general noise, ambient noise and RT60 reverberation from the video endpoint sensors	**Sensor ranges**	Ambient temperature 0 to 35°C at 0.1 degree resolution and plus or minus 2 degrees accuracy; relative humidity 20% to 90% at 1% resolution and plus or minus 10% accuracy; air quality index 1 to 5 at 0.1 resolution and plus or minus 1 accuracy
Pairing	Direct connection to a PoE-enabled network port on the Cisco video device, or remote pairing over LAN by IP	**Registration**	Registers to a Cisco video device by direct or remote pairing, or to the Webex Cloud with a Room Navigator licence

LAYER23-SWITCH

Signaling protocols	TCP/IP	**Height range**	Maximum 5.2 in (13.2 cm) in the vertical position and minimum 3.85 in (9.77 cm) in the lower table position
Security	HTTPS and SSH management, password protection for IP administration and administration access, network settings protection, SRTP media encryption using AES-128-GCM or AES-256-GCM, WPA3 and WPA3-Enterprise with CCMP128, and 802.1x authentication for directly or remotely paired devices	**Digital signage**	Configurable in Control Hub
Accessory part numbers	CS-T10-TS-FT2-G= foot stand spare in First Light and CS-T10-TS-FT2-C= in Carbon Black	**Software compatibility**	RoomOS 9.14.3 or later, certified for Microsoft Teams Rooms Console and Microsoft Teams panel
Power	Power over Ethernet 802.3af Class 0 at 100 to 240 VAC, 0.5A maximum, 50/60 Hz	**Power management**	Configurable office hours to save energy and extend touchscreen life where digital signage, booking and wake-on-motion are active
Dimensions	2.8 x 9.53 x 6.42 in (7.1 x 24.2 x 16.3 cm)	**Storage temperature**	-20°C to 60°C (-4°F to 140°F)
Storage humidity	10% to 90% relative humidity, noncondensing	**Compliance model number**	TTC5-15
Regulatory compliance	Directives 2014/30/EU, 2014/35/EU, 2011/65/EU and 2002/96/EU, NRTL approved, EMC EN 55032 Class A and EN 55024, safety EN 60950-1 and EN 62479, FCC CFR 47 Part 15B Class A		

Get Price and Availability for CS-T10-TS-L-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.