

BRAND NEW & VERIFIED



VERIFIED PRODUCT DATASHEET

PWR-IE50W-AC-L

Cisco Network Hardware Specification, Availability and Quote Reference

| | |
|----------------------|---|
| Product Model | PWR-IE50W-AC-L |
| Document Type | Product Datasheet |
| Condition | Brand New, Original and Verifieded |
| Supplier | Layer23-Switch.com |

| | | | |
|-------------------------------|-------------------------------------|-------------------------------------|-----------------------------------|
| 200+ Countries Sold | 18,000+ Customers Trusted | \$20M Inventory Available | 1-Year Warranty Support |
|-------------------------------|-------------------------------------|-------------------------------------|-----------------------------------|

Need Price or Availability?

View product details, check stock, or request a fast quotation from Layer23-Switch.

[View Product Page & Request a Quote](#)



PWR-IE50W-AC-L Datasheet

The Cisco PWR-IE50W-AC-L datasheet provides verified specifications, key features, and application scenarios. This document helps engineers and IT buyers quickly evaluate the PWR-IE50W-AC-L and integrate it into enterprise or service provider networks with confidence.

[Read More](#) | [Quote](#)

Specification

| Parameter | Specification | Parameter | Specification |
|---------------------------------|----------------------------|---------------------------------|---|
| Model | PWR-IE50W-AC-L | Form factor | Industrial DIN-rail AC to DC power supply |
| Nominal output power | 50W | Output voltage / current | 24-28V DC, 2.1A |
| Holdup time @100% load | 20 ms | Protections | Over Voltage, Over Current, Over Temperature, Short Circuit |
| Rated nominal input (AC) | 100-240V AC, 1.2A, 50/60Hz | Supported input range | AC 90-264V |
| Typical efficiency | 88% | Inrush current (25°C) | <35A @115VAC, <70A @230VAC |
| Operating temperature | -20°C to +70°C | Derating guidance | >55°C: -3.33%/°C; <-10°C: -2%/°C |
| Storage temperature | -40°C to +85°C | Operating humidity | 5-95% RH (non-condensing) |
| IP rating | IP20 | Hazardous locations | Not approved for hazardous location installations |

| Parameter | Specification | Parameter | Specification |
|--------------------------------|---|-----------------|-------------------------------------|
| Dimensions (W x H x D) | 30 x 75 x 89.5 mm (1.18 x 2.95 x 3.52 in) | Weight | 0.18 kg (0.39 lb) |
| MTBF (Telcordia SR-332) | 2,255,613 hours | Cooling | Fanless, natural convection |
| Safety / EMC (summary) | EN/IEC 60950-1, EN/IEC 62368-1, CE, FCC Part 15B; see datasheet for full list | Warranty | Five-year limited hardware warranty |

Want to Buy

[Order Now](#) [Get a Quote](#)

Why Layer23-Switch.com

As a leading network hardware supplier, Layer23-Switch.com focuses on original new ICT equipment of Cisco, H3C, Juniper, etc.

200+

Countries we Sold

18,000+

Customers Trusted

\$20,000,000

Inventory Available

50%-98%

Off Global List Price

100%

Safe Online Shopping

Contact Us

- WhatsApp: [+8617181189993](https://wa.me/8617181189993)
- Wechat: [layer23-switch](https://weixin.qq.com/q/layer23-switch)
- Telegram: [layer23_switch](https://t.me/layer23_switch)
- Email: sales@layer23-switch.com

Need Price and Availability for PWR-IE50W-AC-L?

View product details, request a quote, or check current stock from Layer23-Switch.

[View Product Details & Request a Quote](#)