

CISCO CATALYST 8000 ROUTER MODULES & CARDS

C-NIM-2T

2x100M/1G RJ45/SFP · Catalyst 8200/8300 WAN NIM · MACsec

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C-NIM-2T
Category	Cisco Catalyst 8000 Router Modules & Cards
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO CATALYST 8000 ROUTER MODULES & CARDS

C-NIM-2T

2x100M/1G RJ45/SFP · Catalyst 8200/8300 WAN NIM · MACsec

C-NIM-2T is a Cisco Catalyst 8000 Gigabit Ethernet WAN Network Interface Module for Catalyst 8200, Catalyst 8200L, and Catalyst 8300 edge platforms. It expands a router NIM slot for routed WAN handoffs where copper and fiber media need to be matched in the same branch or edge platform, using two dual-mode 100-Mbps/1-Gbps GE/SFP port groups with one active RJ-45 or SFP media choice per group.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C-NIM-2T	Product type	Dual combo GE/SFP WAN Network Interface Module
Cisco ordering description	Cisco 2-port 100-Mbps/1-Gbps dual-mode GE/SFP Network Interface Module	Ordering form	C-NIM-2T (=)
Form factor	NIM	WAN port design	Two RJ-45/SFP port groups
RJ-45 ports	Two copper line ports	SFP ports	Two fiber ports
Copper media support	100BASE-TX and 1000BASE-T	SFP media support	100BASE-FX and 1000BASE-X
Active media rule	One RJ-45 or SFP port from each group can be used simultaneously	Supported platform family	Catalyst 8200 Series, Catalyst 8200L, and Catalyst 8300 Series
Minimum Cisco IOS XE version	17.6.1	Minimum XE SD-WAN version	17.6.1
Minimum vManage version	20.6.1	WAN MACsec support	256-bit WAN MACsec
Power over Ethernet	No	10G backplane connection	No
Direct NIM-slot service behavior	Online insertion only	C-SM-NIM-ADPT support	C-NIM-2T is listed as supported
SM-X adapter service behavior	Full OIR for supported 1- and 2-port NIMs	Supported SFP scope	Cisco-listed 100M and 1G SFP transceivers for C-NIM-2T
Dimensions	1.25 x 3.50 x 7.24 in. (32 x 89 x 184 mm)	Weight	360 grams
Operating temperature	32 to 104 degrees F (0 to 40 degrees C)	Storage temperature	-38 to 150 degrees F (-40 to 70 degrees C)
Relative humidity	5% to 95%	Operating humidity	5% to 85%

Get Price and Availability for C-NIM-2T

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v30181189993) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH