

CISCO · CATALYST 1200 SWITCHES

C1200-24FP-4X

24x1G PoE+ Ports · 4x10G SFP+ Uplinks · 375W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C1200-24FP-4X
Category	Catalyst 1200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 1200 SWITCHES

C1200-24FP-4X

24x1G PoE+ Ports · 4x10G SFP+ Uplinks · 375W PoE Budget

C1200-24FP-4X is a Cisco Catalyst 1200 Series managed Gigabit Ethernet PoE+ switch built for campus access switching where copper endpoint ports and 10G fiber uplinks are needed in one fixed platform.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	C1200-24FP-4X	Product type	Managed Gigabit Ethernet PoE+ switch
Downlink ports	24 x 10/100/1000 RJ45 PoE+ ports	Uplink interfaces	4 x 10 Gigabit SFP+
Total system ports	28 x Gigabit Ethernet or 10 Gigabit Ethernet interfaces	Default PoE budget	375W power dedicated to PoE
PoE-capable ports	24	Switching capacity	128.0 Gbps
Forwarding rate	95.23 Mpps	Packet buffer	1.5 MB
Management	Cisco Business Dashboard, Cisco Business mobile app, web UI, SNMP	Operating software	Customized Linux OS software
Console port	Cisco Standard RJ-45 console and USB Type C port	USB port	USB Type C file and image management port
Power supply	Internal universal AC	AC input	100 to 240V, 50 to 60 Hz
System power consumption	110V=41.1W; 220V=40.9W	Power consumption with PoE	110V=452.9W; 220V=450.4W
Idle power	110V=22W; 220V=22.7W	Heat dissipation	1544.4 BTU/hr
Fan design	1 fan	Acoustic noise	25 C: 34.8 dBA
MTBF	698,220 hours at 25 C	Dimensions	445 x 345 x 44 mm
Unit weight	4.6 kg	Operating temperature	23 to 122 F (-5 to 50 C)
Storage temperature	-13 to 158 F (-25 to 70 C)	Package contents	Switch, power cord, mounting kit, pointer card
Minimum cable	Category 5e Ethernet network cable		

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM

Get Price and Availability for C1200-24FP-4X

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH