

CISCO · CATALYST 1200 SWITCHES

C1200-24P-4G

24x1G PoE+ Ports · 4x1G SFP Uplinks · 195W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C1200-24P-4G
Category	Catalyst 1200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 1200 SWITCHES

C1200-24P-4G

24x1G PoE+ Ports · 4x1G SFP Uplinks · 195W PoE Budget

The C1200-24P-4G is a Cisco Catalyst 1200 Series fixed managed PoE+ access switch for small-office and branch closets that power a moderate number of phones, cameras and access points. The switch has 24 Gigabit PoE+ ports sharing a 195W budget, four Gigabit SFP uplinks and 56 Gbps of switching capacity in a fanless chassis.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	C1200-24P-4G	Product type	Managed Gigabit Ethernet PoE+ switch
Downlink ports	24 x 10/100/1000 RJ45 PoE+ ports	Uplink ports	4 x Gigabit SFP
Total ports	28 x Gigabit Ethernet	Default PoE budget	195W power dedicated to PoE
PoE-capable ports	24	Per-port PoE support	Up to 30.0W to any Gigabit Ethernet port within the switch PoE budget
Switching capacity	56.0 Gbps	Forwarding rate	41.67 Mpps
Packet buffer	1.5 MB	Active VLANs	Up to 255
Static routing	IPv4/IPv6 static routing	ACL scale	Up to 512 rules
QoS queues	8 hardware queues	Management	Web UI, CLI, Cisco Business Dashboard, Cisco Business mobile app, SNMP
Operating software	Customized Linux OS software	Console port	Cisco Standard RJ-45 console and USB Type C port
Default power supply	Internal universal AC	AC input	100 to 240V, 50 to 60 Hz
System power consumption	110V=25.9W; 220V=27.5W	Power consumption with PoE	110V=235.2W; 220V=230.8W
Idle power	110V=13.5W; 220V=14.8W	Heat dissipation	802 BTU/hr
Fan design	Fanless	MTBF	698,220 hours at 25 C
Dimensions	445 x 299 x 44 mm	Weight	3.53 kg
Operating temperature	23 to 122 F (-5 to 50 C)	Storage temperature	-13 to 158 F (-25 to 70 C)
Package contents	Switch, power cord, mounting kit, pointer card		

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM

Get Price and Availability for C1200-24P-4G

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH