

CISCO · CATALYST 1200 SWITCHES

C1200-48P-4X

48x1G PoE+ Ports · 4x10G SFP+ Uplinks · 375W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C1200-48P-4X
Category	Catalyst 1200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 1200 SWITCHES

C1200-48P-4X

48x1G PoE+ Ports · 4x10G SFP+ Uplinks · 375W PoE Budget

The C1200-48P-4X is a Cisco Catalyst 1200 Series managed Gigabit Ethernet PoE+ switch for access closets that power many endpoints and uplink over 10G fiber. The switch has 48 10/100/1000 PoE+ ports, four 10 Gigabit SFP+ uplinks, a 375W PoE budget and 176 Gbps of switching capacity.

New, factory-sealed · 3-year LSCare warranty · 14-day returns ·
Cisco SN check before shipment

Specifications

Product ID	C1200-48P-4X	Product type	Managed Gigabit Ethernet PoE+ switch
Downlink ports	48 x 10/100/1000 RJ45 PoE+ ports	Uplink ports	4 x 10 Gigabit SFP+
Total ports	48 x Gigabit Ethernet plus 4 x 10 Gigabit Ethernet	Default PoE budget	375W power dedicated to PoE
PoE-capable ports	48	Switching capacity	176.0 Gbps
Forwarding rate	130.94 Mpps	Packet buffer	3 MB
Active VLANs	Up to 255	Static routing	Up to 32 static routes
Layer 3 interfaces	Up to 16 IP interfaces	Management	CLI, on-box web UI, Cisco Business Dashboard, Cisco Business mobile app, SNMP
Operating software	Customized Linux OS software	Console port	Cisco Standard RJ-45 console and USB Type C port
CPU	Dual-core ARM at 1.4 GHz	DRAM	1 GB DDR4
Flash	512 MB	Default power supply	Internal universal AC
AC input	100 to 240V, 50 to 60 Hz	System power consumption	110V=47.44W; 220V=47.03W
Power consumption with PoE	110V=462.84W; 220V=449.48W	Idle power	110V=20.51W; 220V=20.27W
Heat dissipation	1579.28 BTU/hr	Fan design	1 fan
Acoustic noise	25 C: 37.3 dBA	MTBF	856,329 hours at 25 C
Dimensions	445 x 350 x 44 mm	Weight	5.43 kg
Operating temperature	23 to 122 F (-5 to 50 C)	Storage temperature	-13 to 158 F (-25 to 70 C)
Package contents	Switch, power cord, mounting kit, pointer card		

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[View Product Page](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.