

CISCO · CATALYST 1200 SWITCHES

C1200-48T-4X

48x1G Data Ports · 4x10G SFP+ Uplinks · Data-Only Catalyst 1200

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C1200-48T-4X
Category	Catalyst 1200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 1200 SWITCHES

C1200-48T-4X

48x1G Data Ports · 4x10G SFP+ Uplinks · Data-Only Catalyst 1200

C1200-48T-4X is a Cisco Catalyst 1200 Series managed Gigabit Ethernet switch for campus access racks that need 48 copper Gigabit data ports with higher-speed aggregation. It combines 48 x 10/100/1000 data ports, 4 x 10 Gigabit SFP+ uplinks, 176.0 Gbps switching capacity, and a 130.94 Mpps forwarding rate in a data-only model with internal universal AC power and no PoE output budget.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C1200-48T-4X	Product type	Managed Gigabit Ethernet switch
Downlink ports	48 x 10/100/1000 data ports	Uplink interfaces	4 x 10 Gigabit SFP+
Total system ports	48 x Gigabit Ethernet plus 4 x 10 Gigabit Ethernet	PoE profile	Data-only model with no PoE output budget
Switching capacity	176.0 Gbps	Forwarding rate	130.94 Mpps
Packet buffer	3 MB	Active VLANs	Up to 255
Static routing	Up to 32 static routes	Layer 3 interfaces	Up to 16 IP interfaces
ACL scale	Up to 512 rules	QoS queues	8 hardware queues
Management	On-device UI, CLI, Cisco Business Dashboard, Cisco Business mobile app, SNMP	Console port	Cisco Standard RJ-45 console and USB Type C port
Operating software	Customized Linux OS software	Minimum Ethernet cable	Category 5e or higher for 1000BASE-T
CPU	Dual-core ARM at 1.4 GHz	DRAM	1 GB DDR4
Flash memory	512 MB	Power supply	Internal universal AC
AC input	100 to 240V, 50 to 60 Hz	System power consumption	110V=40.01W; 220V=39.77W
Idle power	110V=13.12W; 220V=12.93W	Heat dissipation	136.50 BTU/hr
Fan design	1 fan	Acoustic noise	25 C: 29.7 dBA
MTBF	1,452,667 hours at 25 C	Dimensions	445 x 288 x 44 mm
Unit weight	3.95 kg	Operating temperature	23 to 122 F (-5 to 50 C)
Storage temperature	-13 to 158 F (-25 to 70 C)	Package contents	Switch, power cord, mounting kit, pointer card
Rack mounting	Rack-mountable		

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM

Get Price and Availability for C1200-48T-4X

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.