

CISCO · CATALYST 1300 SWITCHES

C1300-24FP-4X

24x1G PoE+ Ports · 4x10G SFP+ Uplinks · 375W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C1300-24FP-4X
Category	Catalyst 1300 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 1300 SWITCHES

C1300-24FP-4X

24x1G PoE+ Ports · 4x10G SFP+ Uplinks · 375W PoE Budget

The C1300-24FP-4X is a Cisco Catalyst 1300 Series managed Layer 3 Gigabit Ethernet PoE+ switch for branch and small-office access closets that power phones, cameras and access points. The switch has 24 Gigabit PoE+ ports with a 375W PoE budget, 4 x 10G SFP+ uplinks, 128.0 Gbps of switching capacity and a single fan.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C1300-24FP-4X	Product type	Managed Layer 3 Gigabit Ethernet PoE+ switch
Downlink ports	24 x 10/100/1000 RJ45 PoE+ ports	Uplink ports	4 x 10 Gigabit SFP+
Total ports	24 x Gigabit Ethernet plus 4 x 10 Gigabit Ethernet	Default PoE budget	375W power dedicated to PoE
Cisco ordering description	24 x 10/100/1000 30W PoE+ ports, 4 x 10 Gigabit SFP+, rack-mountable	PoE-capable ports	24
PoE standards	802.3at PoE+, 802.3af, Cisco pre-standard PoE	Switching capacity	128.0 Gbps
Forwarding rate	95.23 Mpps	Packet buffer	1.5 MB
Hardware stacking	C1300 Family 1, up to 8 switches in a stack	Layer 3 interfaces	Up to 128 IP interfaces in C1300
IPv4 route scale	Up to 990 dynamic plus static IPv4 routes in C1300	Operating software	Linux-based software
Management	Cisco Business Dashboard, Cisco Business mobile app, web UI, CLI, SNMP	Console port	Cisco standard RJ-45 console port and USB Type C port
Flash	1GB SLC	DRAM	1 GB DDR4 for C1300
CPU	ARM dual-core at 1.5 GHz	Default power supply	Internal universal AC
AC input	100 to 240V, 50 to 60 Hz	System power consumption	110V=40.9W; 220V=40.9W
Power consumption with PoE	110V=454.2W; 220V=441.2W	Idle power	110V=21.9W; 220V=22.5W
Heat dissipation	1548.8 BTU/hr	Acoustic noise	25 C: 39 dBA
MTBF	389,607 hours at 25 C	Chassis size	17.49 x 13.78 x 1.73 in
Weight	4.92 kg (10.84 lb)	Operating temperature	23 to 122 F (-5 to 50 C)
Storage temperature	-13 to 158 F (-25 to 70 C)	Package contents	Switch, power cord, mounting kit, pointer card

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM

Get Price and Availability for C1300-24FP-4X

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.