

CISCO · CATALYST 1300 SWITCHES

C1300-24T-4X

24x1G Data Ports · 4x10G SFP+ Uplinks · Fanless Access Switch

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C1300-24T-4X
Category	Catalyst 1300 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 1300 SWITCHES

C1300-24T-4X

24x1G Data Ports · 4x10G SFP+ Uplinks · Fanless Access Switch

C1300-24T-4X is a Cisco Catalyst 1300 managed Layer 3 Gigabit Ethernet switch for campus and branch access networks that need fixed copper connectivity with high-speed fiber uplinks. The switch provides 24 x 10/100/1000 RJ45 data ports and 4 x 10 Gigabit SFP+ uplinks, with 128.0 Gbps switching capacity and a 95.23 Mpps forwarding rate.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	C1300-24T-4X	Product type	Managed Layer 3 Gigabit Ethernet switch
Downlink ports	24 x 10/100/1000 RJ45 data ports	Uplink interfaces	4 x 10 Gigabit SFP+
Total system ports	24 x Gigabit Ethernet plus 4 x 10G	PoE role	Data-only model with no PoE output budget
Switching capacity	128.0 Gbps	Forwarding rate	95.23 Mpps
Hardware stacking	C1300 Family 1, up to 8 switches in a stack	Packet buffer	1.5 MB
Operating software	Linux-based software	Management	Web UI, CLI, Cisco Business Dashboard, Cisco Business mobile app, SNMP
Console ports	Cisco standard RJ-45 console port and USB Type C port	Flash	1GB SLC
CPU	ARM dual-core at 1.5 GHz	DRAM	1 GB DDR4 for C1300
Power supply	Internal universal AC	AC input	100 to 240V, 50 to 60 Hz
System power consumption	110V=22.3W; 220V=22.4W	Idle power	110V=4.9W; 220V=5.2W
Heat dissipation	76.4 BTU/hr	Fan design	Fanless
MTBF	646,083 hours at 25 C	Unit weight	3.14 kg (6.92 lb)
Operating temperature	23 to 122 F (-5 to 50 C)	Storage temperature	-13 to 158 F (-25 to 70 C)
Package contents	Switch, power cord, mounting kit, pointer card		

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM

Get Price and Availability for C1300-24T-4X

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH