Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO WIRELESS AP

C9115AXI-A

Wi-Fi 6 4x4:4 AP · Internal Antennas · 2.5G PoE Uplink

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock

Product Model	C9115AXI-A
Category	Cisco Wireless AP
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty

CISCO WIRELESS AP

C9115AXI-A

Wi-Fi 6 4x4:4 AP · Internal Antennas · 2.5G PoE Uplink

The C9115AXI-A is a Cisco Catalyst 9115AX Series indoor Wi-Fi 6 access point with four integrated internal antennas for controller-managed campus and branch WLANs. The access point has 4x4 MIMO with four spatial streams, one 100/1000/2500 Multigigabit Ethernet uplink, an RJ-45 console port and a USB 2.0 port.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C9115AXI-A	**Product type**	Indoor Wi-Fi 6 wireless access point
Exact model record	C9115AXI-A listed in Cisco Industry Canada model records	**Ordering pattern**	Full SKU with a regulatory-domain suffix, such as C9115AXI-A
Management model	Controller-based access point	**Minimum software release**	Cisco Unified Wireless Network Software Release 8.9 or later; Cisco IOS XE Software Release 16.11 or later
Supported controllers	Cisco Catalyst 9800 Series, Cisco 3504, 5520, 8540, and Virtual Wireless Controller	**Wireless standard**	Wi-Fi 6 / IEEE 802.11ax
Radio design	Dedicated 2.4 GHz radio and 5 GHz radio	**MIMO profile**	4x4 MIMO with four spatial streams on both bands
Internal antennas	Four integrated dual-band antennas on Catalyst 9115AXI access points	**2.4 GHz antenna gain**	3 dBi peak gain for integrated internal antennas
5 GHz antenna gain	4 dBi peak gain for integrated internal antennas	**Ethernet uplink**	1 x 100/1000/2500 Multigigabit Ethernet RJ-45
Console port	RJ-45 management console port	**USB port**	USB 2.0
Status indicator	Multi-color status LED	**PoE input options**	802.3at PoE+, 802.3bt Cisco UPOE, AIR-PWRINJ6=, 802.3af PoE, or AIR-PWRINJ5=
802.3at feature mode	4x4 radios, 2.5G link speed, USB enabled, and 20.4W max PoE consumption for Catalyst 9115I	**802.3af feature mode**	2x2 radios, 1G link speed, USB disabled, and 13W max PoE consumption
Power negotiation note	LLDP/CDP should be enabled for proper power negotiation	**Dimensions**	8.0 x 8.0 x 1.5 in. (20.3 x 20.3 x 3.8 cm)
Weight	1.98 lb. (0.9 kg)	**Operating temperature**	32 to 122 F (0 to 50 C)
Operating humidity	10% to 90% noncondensing	**Storage temperature**	-22 to 158 F (-30 to 70 C)
Operating altitude test	40 C at 9843 ft.	**Environmental feature shift**	Above 40 C ambient, radios shift from 4x4 to 2x2, Ethernet downgrades to 1G, and USB is disabled
DRAM	2048 MB DRAM and 1024 MB flash	**Mounting bracket options**	AIR-AP-BRACKET-1 low-profile bracket or AIR-AP-BRACKET-2 universal bracket

LAYER23-SWITCH

Get Price and Availability for C9115AXI-A

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch
Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH