

CISCO WIRELESS AP

C9115AXI-B

Wi-Fi 6 4x4:4 AP · Internal Antennas · 2.5G PoE Uplink

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9115AXI-B
Category	Cisco Wireless AP
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO WIRELESS AP

C9115AXI-B**Wi-Fi 6 4x4:4 AP · Internal Antennas · 2.5G PoE Uplink**

C9115AXI-B is a Cisco Catalyst 9115 Series indoor Wi-Fi 6 access point with integrated internal antennas for controller-based campus wireless access in the B regulatory domain. The SKU is part of the C9115AXI-x ordering family and is documented for dual-band 2.4 GHz and 5 GHz operation with 4x4 MIMO and four spatial streams, a 100/1000/2500 Multigigabit Ethernet uplink, RJ-45 console access, and USB 2.0.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	C9115AXI-B	Product Type	Indoor Wi-Fi 6 wireless access point
Exact Model Record	C9115AXI-B listed in Cisco FCC Declaration of Conformity records	Ordering Pattern	C9115AXI-x with x as regulatory-domain suffix
Management Model	Controller-based access point	Software Support	Cisco Unified Wireless Network Software Release 8.9 or later; Cisco IOS XE Software Release 16.11 or later
Supported Controllers	Cisco Catalyst 9800 Series, Cisco 3504, 5520, 8540, and Virtual Wireless Controller	Wireless Standard	Wi-Fi 6 / IEEE 802.11ax
Radio Design	Dedicated 2.4 GHz radio and 5 GHz radio	MIMO Profile	4x4 MIMO with four spatial streams on both bands
Internal Antennas	Four integrated dual-band antennas on C9115AXI models	2.4 GHz Antenna Gain	3 dBi peak gain for integrated internal antennas
5 GHz Antenna Gain	4 dBi peak gain for integrated internal antennas	Ethernet Uplink	1 x 100/1000/2500 Multigigabit Ethernet RJ-45
Console Port	RJ-45 management console port	USB Port	USB 2.0
Status Indicator	Multi-color status LED	PoE Input Options	802.3at PoE+, 802.3bt Cisco UPOE, AIR-PWRINJ6=, 802.3af PoE, or AIR-PWRINJ5=
802.3at Feature Mode	4x4 radios, 2.5G link speed, USB enabled, and 20.4W max PoE consumption for Catalyst 9115I	802.3af Feature Mode	2x2 radios, 1G link speed, USB disabled, and 13W max PoE consumption
Power Negotiation Note	LLDP/CDP should be enabled for proper power negotiation	Dimensions	8.0 x 8.0 x 1.5 in. (20.3 x 20.3 x 3.8 cm)
Weight	1.98 lb. (0.9 kg)	Operating Temperature	32 to 122 F (0 to 50 C)
Operating Humidity	10% to 90% noncondensing	Storage Temperature	-22 to 158 F (-30 to 70 C)
Operating Altitude Test	40 C at 9843 ft.	Environmental Feature Shift	Above 40 C ambient, radios shift from 4x4 to 2x2, Ethernet downgrades to 1G, and USB is disabled
System Memory	2048 MB DRAM and 1024 MB flash	Mounting Bracket Options	AIR-AP-BRACKET-1 low-profile bracket or AIR-AP-BRACKET-2 universal bracket

Get Price and Availability for C9115AXI-B

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.