

CISCO · CATALYST 9200 SWITCHES

C9200-24P-E

24x1G PoE+ Ports · Modular Uplink · 370W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9200-24P-E
Category	Catalyst 9200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9200 SWITCHES

C9200-24P-E

24x1G PoE+ Ports · Modular Uplink · 370W PoE Budget

The C9200-24P-E is a Cisco Catalyst 9200 Series modular-uplink stackable access switch for wiring closets that power phones, cameras and access points. The switch has 24 1G PoE+ ports, a modular uplink slot, a 370W PoE budget on the default PWR-C6-600WAC and 128 Gbps of switching capacity.

New, factory-sealed · 3-year LSCare warranty · 14-day returns ·
Cisco SN check before shipment

Ordering note C9200-24P-E is ordered with a mandatory 3-year Cisco DNA Essentials subscription (C9200-DNA-E). We include it in your quote.

Specifications

Product ID	C9200-24P-E	Product type	Stackable access switch with modular uplinks
Network license	Network Essentials	Downlink ports	24 x 1G PoE+ copper ports
PoE standards	IEEE 802.3at PoE+ up to 30W per port	Uplink architecture	Modular uplink options
Confirmed uplink modules	C9200-NM-4G, C9200-NM-4X, C9200-NM-BLANK	Power supply slots	2 power supply slots
Default primary power supply	PWR-C6-600WAC	AC input range	100 to 240 VAC, 50 to 60 Hz
Default PoE budget	370W with PWR-C6-600WAC	PoE budget with second supply	740W with a second PWR-C6-600WAC
Optional DC power supply	PWR-C6-715WDC= spare supported on C9200 PoE models with IOS XE 17.8.1 and later	Power supply slot rule	Second slot ships with a blank module and must be populated for cooling
Fan modules	Field-replaceable fan modules for C9200 models	Fan spare	FAN-T2= fan module
Stacking architecture	StackWise-160	Stack bandwidth	160 Gbps
Stack kit	C9200-STACK-KIT	Stack members	Up to 8 C9200 models with the same license level
Switching capacity	128 Gbps standalone; 288 Gbps with stacking	Forwarding rate	95.23 Mpps standalone; 214 Mpps with stacking
Virtual networks	4 for C9200-24P-E	MAC addresses	32,000
IPv4 routes	14,000 total with 10,000 direct and 4,000 indirect routes	IPv4 routing entries	4,000
IPv6 routes	2,000	Packet buffer	6 MB for 24- or 48-port Gigabit Ethernet models
Flexible NetFlow entries	16,000 flows on 24- and 48-port Gigabit Ethernet models	DRAM	4 GB
Flash	4 GB	VLAN IDs	4094
Total SVIs	512	Jumbo frames	9198 bytes

Dimensions	1.73 x 17.5 x 13.8 in. (4.4 x 44.4 x 35 cm)	Installed dimensions	1.73 x 17.5 x 15.4 in. (4.4 x 44.4 x 39.1 cm) with fan FRUs and power supplies installed
Weight	5 kg (11 lb) with one power supply installed	Operating temperature	-5°C to 45°C (23°F to 113°F)
Operating altitude	Up to 10,000 ft (3000 m)	Minimum software release	Cisco IOS XE Gibraltar 16.10.1

Optional Add-ons

Add-on	Cisco PID	Purpose
Network Module	C9200-NM-4G	4x1G SFP Uplinks - Network Module - Catalyst 9200 Modular Switches
Network Module	C9200-NM-4X	4x10GE SFP+ Ports - Catalyst 9200 Module
Power Supply / Fan	PWR-C6-600WAC	600W AC PSU - Catalyst 9200 PoE Models
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-SR	10GBASE-SR SFP+ - 850nm MMF - 400m OM4
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-10G-LR	10GBASE-LR SFP+ - 1310nm SMF - 10km Reach
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM
Optics	GLC-ZX-SMD	1000BASE-ZX SFP - 70km SMF - EXT DOM
Cable / Stacking Kit	C9200-STACK-KIT	StackWise-160 Bandwidth - 2 Adapters and Cable - Catalyst 9200 Stack Kit
Cable / Stacking Kit	STACK-T4-50CM	50 cm Data Stack Cable - Catalyst 9200 and 9200L Stack Kit Default
Cable / Stacking Kit	STACK-T4-1M	1 m Data Stack Cable - Catalyst 9200 and 9200L - StackWise-160/80
Cable / Stacking Kit	STACK-T4-3M	3 m Type 3 Stacking Cable - Catalyst 9200 and 9200L - StackWise-160/80

Get Price and Availability for C9200-24P-E

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH