

CISCO · CATALYST 9200 SWITCHES

C9200CX-12T-2X2G-A

12x1G Data Ports · 2x10G SFP+ Uplinks · PD/Adapter Powered · Network Advantage

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9200CX-12T-2X2G-A
Category	Catalyst 9200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9200 SWITCHES

C9200CX-12T-2X2G-A

12x1G Data Ports · 2x10G SFP+ Uplinks · PD/Adapter Powered · Network Advantage

The C9200CX-12T-2X2G-A is a Cisco Catalyst 9200CX Series compact access switch for wall, DIN-rail and under-desk installs outside the wiring closet. The switch has 12 10/100/1000 data ports, two 10G SFP+ uplinks, two 1G copper uplinks and 70 Gbps of switching capacity, and it takes power from an 802.3bt Class 6 PD uplink at up to 51W or an optional 80W adapter.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Ordering note C9200CX-12T-2X2G-A is ordered with a mandatory 3-year Cisco DNA Advantage subscription (C9200-DNA-A). We include it in your quote.

Specifications

Product ID	C9200CX-12T-2X2G-A	Network license	Network Advantage
Data ports	12x 10/100/1000	Copper uplinks	2x 1G fixed + 1x 1G copper PD uplink (802.3bt Class 6)
Fiber uplinks	2x 10G SFP+ fixed	PD input power	Up to 51W via 802.3bt Class 6 powered-device uplink
Auxiliary power adapter	Optional 80W AC-DC (C9K-80W-ADPT / PWR-ADPT) or 80W DC-DC (C9K-ADPT-DC)	Power source priority	Auxiliary adapter takes priority over PD; PD port disabled when adapter is connected
Switching capacity	70 Gbps	Forwarding rate	52.08 Mpps
MAC addresses	32,000	IPv4 routes (ARP + learned)	14,000 (10,000 direct + 4,000 indirect)
IPv4 routes	4,000	IPv6 routes	2,000
Multicast routes	1,000	ACL entries	1,600
QoS entries	1,000	Packet buffer	6 MB
FNF flows	16,000	DRAM / flash	4 GB / 8 GB (plus up to 4 GB Micro-SD expansion)
VLAN IDs	4094	Jumbo frames	9198 bytes
SVI	512	PVST instances	128
SD-Access virtual networks	16	Stacking	Not supported
Fan modules	Fanless	Console port	USB Micro-B (CAB-CON-USBRJ45 adapter available for RJ45)
Dimensions	1.73 x 10.6 x 6.5 in (4.4 x 26.9 x 16.5 cm)	Weight	4.0 lb / 1.81 kg (datasheet); Cisco hardware installation guide lists 4.1 lb / 1.86 kg
Operating temperature	-5°C to 45°C (23°F to 113°F)	Storage temperature	-40°C to 70°C (-40°F to 158°F)

Operating humidity	5% to 90% noncondensing	Operating altitude	Up to 10,000 ft (3000 m)
MTBF	960,180 hours	Mounting	Magnetic tray, DIN rail, 19-inch rack bracket, wall-mount tray, under-desk mount, tabletop rubber feet
Safety certifications	IEC/UL/CSA/EN 60950-1 and 62368-1, AS/NZS 60950.1/62368.1, Class I Equipment	EMC certifications	CISPR 32/35 Class A, EN 55032/55035, FCC Part 15, ICES-003 Class A
Environmental compliance	RoHS 5		

Get Price and Availability for C9200CX-12T-2X2G-A

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3070123456789) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.