

CISCO · CATALYST 9200 SWITCHES

C9200L-24P-4G-A

24x1G PoE+ Ports · 4x1G SFP Uplinks · 370W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9200L-24P-4G-A
Category	Catalyst 9200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9200 SWITCHES

C9200L-24P-4G-A

24x1G PoE+ Ports · 4x1G SFP Uplinks · 370W PoE Budget

The C9200L-24P-4G-A is a Cisco Catalyst 9200L fixed-uplink stackable access switch for wiring closets that power phones and access points over PoE+. The switch has 24 1G PoE+ ports and four fixed 1G SFP uplinks, with a 370W PoE budget from its default PWR-C5-600WAC supply, 740W with a second one, and StackWise-80 at 80 Gbps.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Ordering note C9200L-24P-4G-A is ordered with a mandatory 3-year Cisco DNA Advantage subscription (C9200-DNA-A). We include it in your quote.

Specifications

Product ID	C9200L-24P-4G-A	Product type	Fixed-uplink stackable access switch
Network license	Network Advantage	Downlink ports	24 x 1G PoE+ copper ports
Uplink ports	4 x 1G SFP fixed uplink ports	Modular uplinks	No for C9200L fixed-uplink models
Power supply slots	2 slots	Default power supply	PWR-C5-600WAC
Fan design	2 fixed fans with redundancy support	Stacking architecture	StackWise-80
Stack bandwidth	80 Gbps	Supported stack members	Other C9200L models with the same license level
Switching capacity	56 Gbps standalone; 136 Gbps with stacking	Forwarding rate	41.67 Mpps standalone; 101 Mpps with stacking
PoE standards	IEEE 802.3at PoE+ up to 30W per port	Default PoE budget	370W with PWR-C5-600WAC
PoE budget with second supply	740W with second PWR-C5-600WAC	Optional DC power supply	PWR-C5-715WDC= spare supported on C9200L PoE models with IOS XE 17.8.1 and later
DRAM	2 GB	Flash	4 GB
MAC addresses	16,000	IPv4 routes	11,000 total with 8,000 direct and 3,000 indirect routes
Packet buffer	6 MB for 24- or 48-port Gigabit Ethernet C9200L models	Flexible NetFlow entries	16,000 flows on 24- and 48-port Gigabit Ethernet models
Dimensions	1.73 x 17.5 x 11.3 in. (4.4 x 44.5 x 28.8 cm)	Installed dimensions	1.73 x 17.5 x 12.9 in. (4.4 x 44.5 x 32.9 cm) with fan FRUs and power supplies installed
Weight	4.71 kg (10.4 lb) with one power supply installed	Operating temperature	-5°C to 45°C (23°F to 113°F)
Operating altitude	Up to 10,000 ft (3000 m)	MTBF	392,210 hours

Optional Add-ons

Add-on	Cisco PID	Purpose
Power Supply / Fan	PWR-C5-600WAC	600W AC PSU - Catalyst 9200L PoE Models
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM
Optics	GLC-ZX-SMD	1000BASE-ZX SFP - 70km SMF - EXT DOM
Cable / Stacking Kit	C9200L-STACK-KIT	StackWise-80 Bandwidth - 2 Adapters and Cable - Catalyst 9200L Stack Kit
Cable / Stacking Kit	STACK-T4-50CM	50 cm Data Stack Cable - Catalyst 9200 and 9200L Stack Kit Default -
Cable / Stacking Kit	STACK-T4-1M	1 m Data Stack Cable - Catalyst 9200 and 9200L - StackWise-160/80
Cable / Stacking Kit	STACK-T4-3M	3 m Type 3 Stacking Cable - Catalyst 9200 and 9200L - StackWise-160/80

**Get Price and Availability for
C9200L-24P-4G-A**

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)[View Product Page](#)

Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.