

CISCO · CATALYST 9200 SWITCHES

C9200L-24T-4X-A

24x1G Data Ports · Fixed 4x10G Uplinks · Network Advantage

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9200L-24T-4X-A
Category	Catalyst 9200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9200 SWITCHES

C9200L-24T-4X-A

24x1G Data Ports · Fixed 4x10G Uplinks · Network Advantage

The C9200L-24T-4X-A is a Cisco Catalyst 9200L Series fixed-uplink access switch for data-only wiring closets that need Layer 3 segmentation and a 10G handoff. The switch has 24 10/100/1000 data ports with no PoE, four fixed 1G SFP or 10G SFP+ uplinks, 128 Gbps of switching capacity and a 125W PWR-C5-125WAC supply, with Network Advantage as its license tier.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Ordering note C9200L-24T-4X-A is ordered with a mandatory 3-year Cisco DNA Advantage subscription (C9200-DNA-A). We include it in your quote.

Specifications

Product ID	C9200L-24T-4X-A	PID description	Catalyst 9200L 24-port Data 4x10G uplink Switch, Network Advantage
Network license	Network Advantage	Minimum software release	Cisco IOS XE 16.9.x
Data ports	24x 10/100/1000 RJ-45 (4-pair Cat 5E UTP)	Uplink ports	4x fixed, 1000BASE-SX/-LX/LH/-ZX/-BX10/DWDM/CWDM SFP or 10GBASE-SR/LR/ER/ZR/DWDM SFP+
Management port	Ethernet management port, RJ-45 (Cat 5)	Console port	RJ-45 or mini-USB (RJ-45-to-DB9 cable, USB-C/USB adapter)
Switching capacity	128 Gbps (208 Gbps stacked)	Forwarding rate	95.23 Mpps (155 Mpps stacked)
Packet buffer	6 MB	DRAM / flash	2 GB / 4 GB
MAC addresses	16,000 entries	IPv4 routes	3,000 (11,000 ARP + learned)
IPv6 routes	1,500 entries	Multicast routes	1,000 entries
ACL entries	1,500 entries	QoS entries	1,000 entries
VLAN IDs	4094	SVIs / PVST instances	512 / 128
Flexible NetFlow flows	16,000	Jumbo frame size	9198 bytes
Default power supply	PWR-C5-125WAC (125W AC)	Power supply slots	2 (dual FRU, second supply optional for redundancy)
Power supply input	100-240 VAC autoranging, 50-60Hz	Power supply output heat	426.5 BTU/hr
PoE support	No PoE output (data-only ports)	Fan modules	Fixed redundant fans
Stacking	StackWise-80, 80 Gbps, up to 8 members	Stack cable	C9200L-STACK-KIT; 0.5m default, 1m/3m optional
Operating temperature	-5 to 45°C (up to 1500m); -5 to 40°C (up to 3000m)	Storage temperature	-40 to 70°C
Operating humidity	5%-90% non-condensing	Operating altitude	Up to 10,000 ft (3000m)
Acoustic noise	LpA 42 dB typical / 45 dB max	Dimensions (H x W x D)	1.73 x 17.5 x 11.3 in chassis-only; 12.9 in with fan endplate
Weight	4.35 kg (9.59 lb)	MTBF	525,990 hours

Safety certifications	IEC/UL/CSA/EN 60950-1 and 62368-1, AS/NZS 60950.1/62368.1, Class I Equipment	EMC certifications	CISPR 32 Class A, EN 55032 Class A, FCC Part 15, and related regional EMC standards
Environmental compliance	RoHS 5		

Optional Add-ons

Add-on	Cisco PID	Purpose
Second power supply	PWR-C5-125WAC	Adds power redundancy to the empty PSU slot.
Stack kit	C9200L-STACK-KIT	Provides the stack adapters and cable needed to join this switch into a StackWise-80 stack.
Stack cable, 1m	STACK-T4-1M	Extends stacking cable reach beyond the default 0.5m for non-adjacent rack positions.
Stack cable, 3m	STACK-T4-3M	Extends stacking cable reach for larger rack spans.

**Get Price and Availability for
C9200L-24T-4X-A**

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

[View Product Page](#)

Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.