

CISCO · CATALYST 9200 SWITCHES

C9200L-48PXG-4X-E

12xmGig plus 36x1G PoE+ Ports · 4x10G SFP+ Uplinks · 740W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9200L-48PXG-4X-E
Category	Catalyst 9200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9200 SWITCHES

C9200L-48PXG-4X-E

12xmGig plus 36x1G PoE+ Ports · 4x10G SFP+ Uplinks · 740W PoE Budget

The C9200L-48PXG-4X-E is a Cisco Catalyst 9200L Series fixed-uplink access switch for closets that power Wi-Fi access points and cameras over multigigabit copper. The switch has 12 multigigabit and 36 1G PoE+ ports, four fixed 10G SFP+ uplinks, 392 Gbps of switching capacity and a 740W PoE budget on its default PWR-C5-1KWAC supply.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Ordering note C9200L-48PXG-4X-E is ordered with a mandatory 3-year Cisco DNA Essentials subscription (C9200-DNA-E). We include it in your quote.

Specifications

Product ID	C9200L-48PXG-4X-E	Product type	Fixed-uplink stackable access switch
Network license	Network Essentials	Access port layout	12 x mGig PoE+ ports and 36 x 1G PoE+ ports
Multigigabit ports	12 ports up to 10G, IEEE 802.3bz, full duplex only	1G access ports	36 x 1G PoE+ ports
Fixed uplinks	4 x 10G SFP+ fixed uplink ports	Modular uplinks	No modular uplink network modules on C9200L fixed-uplink models
Power supply slots	2 slots	Default power supply	PWR-C5-1KWAC
PoE standards	IEEE 802.3at PoE+ up to 30W per port	Default PoE budget	740W with PWR-C5-1KWAC
PoE budget with second supply	1440W with second PWR-C5-1KWAC	Optional DC power supply	PWR-C5-715WDC= spare, 485W single / 970W dual, requires IOS XE 17.8.1 or later
Fan design	2 fixed fans	Stacking architecture	StackWise-80
Stack bandwidth	80 Gbps	Maximum stack members	Up to 8 C9200L members at the same license level
Switching capacity	392 Gbps standalone; 472 Gbps with stacking	Forwarding rate	291.66 Mpps standalone; 351 Mpps with stacking
Packet buffer	12 MB on 24- and 48-port multigigabit models	Flexible NetFlow entries	32,000 flows on 24- and 48-port multigigabit models
Introductory software release	Cisco IOS XE Gibraltar 16.11.1	Smart Licensing	Requires a Cisco Smart Account for license use
VLAN IDs	4094	Jumbo frames	9198 bytes
Operating temperature	-5 to 45°C (up to 1500 m); -5 to 40°C (up to 3000 m)	Storage temperature	-40 to 70°C
Operating humidity	5%-90% noncondensing	Operating altitude	Up to 3000 m (10,000 ft)
Acoustic noise	LpA 42 dB typical / 45 dB max	Copper connectors	RJ-45 1000BASE-T

Optical connectors	SFP/SFP+ up to 10GBASE-ER/ZR/DWDM (LC)	Compliance	IEC/UL/CSA/EN 60950-1 and 62368-1 safety; CISPR 32/EN 55032 Class A EMC; RoHS 5
Dimensions	1.73 x 17.5 x 13.8 in (4.4 x 44.5 x 35.0 cm)	Installed dimensions	1.73 x 17.5 x 15.4 in (4.4 x 44.5 x 39.1 cm)
Weight	5.71 kg (12.6 lb) with one power supply installed	MTBF	337,360 hours

Optional Add-ons

Add-on	Cisco PID	Purpose
Power Supply / Fan	PWR-C5-1KWAC	1KW AC PSU - Catalyst 9200L 48-Port PoE
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-SR	10GBASE-SR SFP+ - 850nm MMF - 400m OM4
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-10G-LR	10GBASE-LR SFP+ - 1310nm SMF - 10km Reach
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM
Cable / Stacking Kit	C9200L-STACK-KIT	StackWise-80 Bandwidth - 2 Adapters and Cable - Catalyst 9200L Stack Kit
Cable / Stacking Kit	STACK-T4-50CM	50 cm Data Stack Cable - Catalyst 9200 and 9200L Stack Kit Default
Cable / Stacking Kit	STACK-T4-1M	1 m Data Stack Cable - Catalyst 9200 and 9200L - StackWise-160/80
Cable / Stacking Kit	STACK-T4-3M	3 m Type 3 Stacking Cable - Catalyst 9200 and 9200L - StackWise-160/80

Get Price and Availability for C9200L-48PXG-4X-E

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](tel:+8617181189993) WeChat [layer23-switch](https://www.layer23-switch.com) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.