

CISCO · CATALYST 9200 SWITCHES

C9200L-48T-4G-A

48x1G Data Ports · Fixed 4x1G Uplinks · Network Advantage

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9200L-48T-4G-A
Category	Catalyst 9200 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9200 SWITCHES

C9200L-48T-4G-A

48x1G Data Ports · Fixed 4x1G Uplinks · Network Advantage

The C9200L-48T-4G-A is a Cisco Catalyst 9200L fixed-uplink access switch carrying Network Advantage on 48 non-PoE copper data ports, built for wiring closets that need Advantage-tier routing and segmentation but never plan to run the uplinks past 1G.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Ordering note C9200L-48T-4G-A is ordered with a mandatory 3-year Cisco DNA Advantage subscription (C9200-DNA-A). We include it in your quote.

Specifications

Product ID	C9200L-48T-4G-A	Network license	Network Advantage
Access ports	48 x 10/100/1000 Mbps data copper ports (RJ-45, 4-pair Cat 5E UTP)	Uplink ports	4 x fixed SFP ports, 1G optics only
Management port	RJ-45 Ethernet management port (Cat 5)	Console port	RJ-45 or mini-USB (USB-C/USB adapter)
Switching capacity	104 Gbps standalone; 184 Gbps with StackWise-80 stacking	Forwarding rate	77.38 Mpps standalone; 137 Mpps with stacking
MAC address table	16,000 entries	IPv4 routing entries	3,000 entries (11,000 IPv4 routes with ARP/learned)
IPv6 routing entries	1,500 entries	Multicast routes	1,000 entries
ACL / QoS scale	1,500 ACL entries; 1,000 QoS entries	VLAN IDs	4094
Packet buffer	6 MB	FNF flows	16,000
DRAM / Flash	2 GB DRAM; 4 GB flash	Jumbo frame	9198 bytes
Default power supply	PWR-C5-125WAC (125W AC)	Power supply slots	2 slots, FRU
Power input	100-240 VAC, 50-60 Hz, IEC 320-C14 inlet	Power output / BTU	12V @ 10.5A; 426.5 BTU/hr
PoE support	None	Fan design	2 fixed fans (non-field-replaceable)
Stacking architecture	StackWise-80, up to 8 members, single virtual switch	Stacking accessory	C9200L-STACK-KIT (two data stack adapters, one cable)
Operating temperature	-5C to 45C (up to 1500 m); -5C to 40C (up to 3000 m)	Storage temperature	-40C to 70C
Humidity / Altitude	5%-90% noncondensing; up to 3000 m operating	Acoustic noise	LpA 42 dB typical / 45 dB max; LwA 5.3 B typical / 5.6 B max
Physical dimensions	1.73 x 17.5 x 11.3 in chassis (12.9 in with fan/power extension)	Weight	9.97 lb (4.53 kg), single power supply
Safety certifications	IEC/UL/CSA/EN 60950-1 and 62368-1, AS/NZS 60950.1/62368.1, Class I Equipment	EMC certifications	FCC Part 15, CISPR 32 Class A, EN 55032 Class A, EN 300 386, ICES-003 Class A, CISPR 35, EN 55035

Environmental compliance	RoHS 5	MTBF	508,700 hours
Minimum software release	Cisco IOS XE Fuji 16.9.2		

Optional Add-ons

Add-on	Cisco PID	Purpose
Power Supply / Fan	PWR-C5-125WAC	125W AC PSU - Catalyst 9200L Data Switches
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM
Optics	GLC-ZX-SMD	1000BASE-ZX SFP - 70km SMF - EXT DOM
Cable / Stacking Kit	C9200L-STACK-KIT	StackWise-80 Bandwidth - 2 Adapters and Cable - Catalyst 9200L Stack Kit
Cable / Stacking Kit	STACK-T4-50CM	0.5m StackWise Cable - Catalyst 9200 / 9300
Cable / Stacking Kit	STACK-T4-1M	1m StackWise Cable - Catalyst 9200 / 9300
Cable / Stacking Kit	STACK-T4-3M	3m StackWise Cable - Catalyst 9200 / 9300

**Get Price and Availability for
C9200L-48T-4G-A**

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)[View Product Page](#)

Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.