

CISCO · CATALYST 9300 SWITCHES

C9300-48P-A

48x1G PoE+ Ports · Modular Uplink · 437W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9300-48P-A
Category	Catalyst 9300 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9300 SWITCHES

C9300-48P-A

48x1G PoE+ Ports · Modular Uplink · 437W PoE Budget

The C9300-48P-A is a Cisco Catalyst 9300 Series stackable access switch for wiring closets that power IP phones, access points and cameras over PoE+. The switch has 48 10/100/1000 PoE+ ports with a 437W default PoE budget, a modular uplink slot and 256 Gbps of switching capacity, with Network Advantage built in.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Ordering note C9300-48P-A is ordered with a mandatory 3-year Cisco DNA Advantage subscription (C9300-DNA-A). We include it in your quote.

Specifications

Product ID	C9300-48P-A	Network license	Network Advantage
Total ports	48x 10/100/1000 Mbps copper	PoE standards	Cisco PoE+
Default PoE budget	437W (PWR-C1-715WAC-P)	Maximum PoE budget with secondary supply	Up to 1440W with second 1100W/1900W supply
Uplinks	Modular uplink network module slot	Stacking	StackWise-480, up to 8 members, 480 Gbps/stack
StackPower	Supported, up to 4-member ring (8 with XPS-2200)	Switching capacity	256 Gbps standalone / 736 Gbps stacked
Forwarding rate	190.48 Mpps standalone / 547.62 Mpps stacked	MAC addresses	32,000 entries
IPv4 routes	32,000 (24,000 connected + 8,000 indirect)	IPv6 routes	16,000 entries
Multicast routes	8,000 entries	QoS / ACL entries	5,120 QoS / 5,120 ACL entries
VLAN IDs	4094	SVIs	1000
Jumbo frames	9198 bytes	DRAM / flash	8 GB DRAM / 16 GB Flash
Default power supply	PWR-C1-715WAC-P, 715W AC, 2,440 BTU/hr output	Power redundancy	2 internal supply slots, dual redundant supported
Fan modules	3x field-replaceable, N+1 redundant (FAN-T2=)	Peak power draw (100% PoE, 115VAC)	563.2W with no module / 568.8W with C9300-NM-8X
Chassis dimensions (default supply)	1.73 x 17.5 x 17.7 in	Unit weight (default supply)	7.59 kg (16.73 lb)
MTBF	277,770 hours	Minimum software release	Cisco IOS XE Release 16.5.1a
Operating temperature	-5C to 45C (up to 1500m)	Storage temperature	-40C to 70C
Operating humidity	5%-90% non-condensing	Operating / storage altitude	10,000 ft / 15,000 ft
Acoustic noise (24 PoE+ ports loaded)	45 dB typical / 48 dB max LpA	Management interfaces	RJ-45 Ethernet mgmt, RJ-45 console, USB mini-Type B console

Connector types	RJ-45 (1000BASE-T), LC (SFP/SFP+)	Standards supported	IEEE 802.1x, 802.3af/at, 802.1Q, 802.3az; RMON I/II; SNMPv1/v2c/v3
Safety certifications	UL 60950-1, CAN/CSA-C22.2 No. 60950-1, IEC 60950-1, AS/NZS 60950.1	EMC certifications	FCC Part 15, EN 55032/CISPR 32 Class A, EN 55035, ICES-003 Class A
Environmental compliance	RoHS 5		

Optional Add-ons

Add-on	Cisco PID	Purpose
Network Module	C9300-NM-2Y	2x25G/10G/1G SFP28 Ports - Catalyst 9300 Module
Network Module	C9300-NM-2Q	2x40G QSFP+ Uplinks - Catalyst 9300 Module
Network Module	C9300-NM-4G	4x1GE SFP Ports - Catalyst 9300 Module
Network Module	C9300-NM-4M	4x10G/mGig Copper Ports - Catalyst 9300 Module
Network Module	C9300-NM-8X	8x10G/1G SFP+ Uplinks - Network Module - Catalyst 9300
Power Supply / Fan	PWR-C1-715WAC-P	715W AC PSU - Catalyst 9300 C1 - Platinum Rated
Power Supply / Fan	PWR-C1-1100WAC-P	1100W AC PSU - Catalyst 9300 C1 - Platinum Rated
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-SR	10GBASE-SR SFP+ - 850nm MMF - 400m OM4
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-10G-LR	10GBASE-LR SFP+ - 1310nm SMF - 10km Reach
Optics	SFP-25G-SR-S	25GBASE-SR SFP28 - 850nm MMF - 100m OM4
Optics	SFP-10/25G-LR-S	10/25GBASE-LR SFP28 - 10 km G.652 SMF - 0 to 70°C Commercial Temperature
Optics	QSFP-40G-SR4	40G SR4 QSFP - MPO-12 MMF - 4x10G Breakout
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach

Get Price and Availability for C9300-48P-A

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.