

CISCO · CATALYST 9300 SWITCHES

C9300L-24T-4X-A

24x1G Data Ports · 4x10G Fixed Uplinks

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9300L-24T-4X-A
Category	Catalyst 9300 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9300 SWITCHES

C9300L-24T-4X-A

24x1G Data Ports · 4x10G Fixed Uplinks

C9300L-24T-4X-A is a Cisco Catalyst 9300L fixed-uplink stackable access switch for campus access deployments that need 24 data-only 10/100/1000 copper ports and four integrated 10G/1G SFP+ uplinks.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Ordering note C9300L-24T-4X-A is ordered with a mandatory 3-year Cisco DNA Advantage subscription (C9300-DNA-A). We include it in your quote.

Specifications

Product ID	C9300L-24T-4X-A	Product type	Fixed-uplink stackable access switch
Network license	Network Advantage	Introductory software release	Cisco IOS XE Gibraltar 16.11.1c
Access ports	24 x 10/100/1000 Mbps data copper ports	Uplink ports	4 x 10G/1G SFP+ fixed uplink ports
PoE support	No PoE	Default power supply	PWR-C1-350WAC-P
Modular uplinks	No for C9300L fixed-uplink models	Power supply slots	2 internal power supply module slots
Stacking architecture	StackWise-320	Stacking bandwidth	320 Gbps
Supported stack family	Catalyst 9300L and 9300LM fixed-uplink models	Optional stack accessories	C9300L-STACK-A with STACK-T3A cable options
Switching capacity	128 Gbps standalone	Switching capacity with stacking	448 Gbps
Forwarding rate	95.23 Mpps standalone	Forwarding rate with stacking	333.33 Mpps
MAC addresses	32,000	IPv4 routes	32,000 total with 24,000 direct and 8,000 indirect routes
Packet buffer	16 MB for C9300L 24- and 48-port Gigabit Ethernet models	Flexible NetFlow entries	64,000 flows on C9300L 24- and 48-port Gigabit Ethernet models
DRAM	8 GB	Flash	16 GB
VLAN IDs	4094	Jumbo frames	9198 bytes
Dimensions	1.73 x 17.5 x 19.2 in. (4.4 x 44.5 x 48.8 cm)	Weight	14.93 lb (6.78 kg) with default power supply

Optional Add-ons

Add-on	Cisco PID	Purpose
Power Supply / Fan	PWR-C1-350WAC-P	350W AC PSU - Catalyst 9300 C1 - Platinum Rated
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-SR	10GBASE-SR SFP+ - 850nm MMF - 400m OM4
Optics	SFP-10G-SR-X	10GBASE-SR SFP+ - Extended Temp - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-10G-LR	10GBASE-LR SFP+ - 1310nm SMF - 10km Reach
Optics	SFP-10G-LR-X	10GBASE-LR SFP+ - Extended Temp - 10km SMF
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM

Get Price and Availability for C9300L-24T-4X-A

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.