

CISCO · CATALYST 9300 SWITCHES

C9300L-24T-4X-M

24x1G Data Ports · 4x10G Fixed Uplinks

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9300L-24T-4X-M
Category	Catalyst 9300 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9300 SWITCHES

C9300L-24T-4X-M

24x1G Data Ports · 4x10G Fixed Uplinks

C9300L-24T-4X-M is a Cisco Catalyst 9300L-M fixed-uplink stackable access switch for Meraki-managed campus access deployments. It provides 24 1G data access ports and four fixed 10G/1G SFP+ uplinks, uses the PWR-C1-350WAC-P-M default power supply, and is managed through the Cisco Meraki Dashboard with Meraki Advanced or Enterprise software options.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	C9300L-24T-4X-M	Product type	Fixed-uplink stackable access switch
Software option	Meraki Advanced or Enterprise	Management mode	Cisco Meraki Dashboard
Meraki license terms	1, 3, 5, 7, or 10 years	Access ports	24 x 1GbE data ports
Uplink ports	4 x 10G/1G SFP+ fixed uplink ports	PoE support	Not applicable for C9300L-24T data model
Default power supply	PWR-C1-350WAC-P-M	Power supply configuration	Hot-swappable dual power supply support
Power load	56.85 W idle; 73.54 W maximum	Stacking architecture	StackWise-320
Stacking kit	C9300L-STAK-KIT2-M required for intended stacks	Hardware stack ports	2
Dedicated management interface	1	Switching capacity	128 Gbps standalone
Switching capacity with stacking	448 Gbps	Forwarding rate	95.23 Mpps standalone
Forwarding rate with stacking	333.33 Mpps	MAC forwarding entries	32,000
VLAN IDs	4094	Mount type	1U rack mount
Hot swap fans	3	Dimensions	1.73 x 17.5 x 17.7 in. (4.4 x 44.5 x 44.9 cm)
Weight	14.93 lb (6.78 kg) with default power supply	Operating temperature	-5 C to 45 C
Humidity	5 to 90%		

Optional Add-ons

Add-on	Cisco PID	Purpose
Power Supply / Fan	PWR-C1-350WAC-P	350W AC PSU - Catalyst 9300 C1 - Platinum Rated
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-SR	10GBASE-SR SFP+ - 850nm MMF - 400m OM4

Optics	SFP-10G-SR-X	10GBASE-SR SFP+ - Extended Temp - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-10G-LR	10GBASE-LR SFP+ - 1310nm SMF - 10km Reach
Optics	SFP-10G-LR-X	10GBASE-LR SFP+ - Extended Temp - 10km SMF
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM

Get Price and Availability for C9300L-24T-4X-M

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a96700000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.