

CISCO · CATALYST 9300 SWITCHES

C9300L-48UXG-4X-M

12x10G mGig + 36x1G UPOE · 4x10G Fixed Uplinks · Meraki · 675W PoE Budget

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9300L-48UXG-4X-M
Category	Catalyst 9300 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9300 SWITCHES

C9300L-48UXG-4X-M

12x10G mGig + 36x1G UPOE · 4x10G Fixed Uplinks · Meraki · 675W PoE Budget

C9300L-48UXG-4X-M is a Cisco Catalyst 9300L-M fixed-uplink UPOE access switch for Meraki-managed campus access networks.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C9300L-48UXG-4X-M	Product type	Fixed-uplink stackable UPOE access switch
Management mode	Cisco Meraki Dashboard	Software option	Meraki Advanced or Enterprise
Meraki license terms	1, 3, 5, 7, or 10 years	Access ports	12 x mGig plus 36 x GbE copper ports
mGig speeds	100M, 1G, 2.5G, 5G, and 10G	GbE port speeds	10M, 100M, and 1G
Uplink ports	4 x 10G/1G SFP+ fixed uplink ports	PoE capability	60W UPOE
Default PoE budget	675W with primary power supply	Default power supply	PWR-C1-1100WAC-P-M
Power supply configuration	Hot-swappable dual power supply support	Secondary PoE value	1775W with secondary power-supply condition
Power load	104.56 W idle; 875.3 W maximum	Power input range	115V to 240V AC, 50 to 60 Hz for 1100W AC supply
Stacking architecture	StackWise-320	Stacking kit	C9300L-STAK-KIT2-M required for intended stacks
Hardware stack ports	2	Dedicated management interface	1
Switching capacity	392 Gbps standalone	Switching capacity with stacking	712 Gbps
Forwarding rate	291.66 Mpps standalone	Forwarding rate with stacking	529.76 Mpps
Dimensions	1.73 x 17.5 x 19.2 in. (4.4 x 44.5 x 48.8 cm)	Weight	16.86 lb (7.65 kg) with default power supply
Mount type	1U rack mount	Hot swap fans	3
Operating temperature	-5 deg C to 45 deg C	Humidity	5 to 90%
MTBF at 25 deg C	273,820 hours		

Optional Add-ons

Add-on	Cisco PID	Purpose
Power Supply / Fan	PWR-C1-1100WAC-P	1100W AC PSU - Catalyst 9300 C1 - Platinum Rated
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF

Optics	SFP-10G-SR	10GBASE-SR SFP+ - 850nm MMF - 400m OM4
Optics	SFP-10G-SR-X	10GBASE-SR SFP+ - Extended Temp - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-10G-LR	10GBASE-LR SFP+ - 1310nm SMF - 10km Reach
Optics	SFP-10G-LR-X	10GBASE-LR SFP+ - Extended Temp - 10km SMF
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM
Optics	GLC-EX-SMD	1000BASE-EX SFP - 40km SMF - DOM

Get Price and Availability for C9300L-48UXG-4X-M

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3071-23switch) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.