

CISCO · CATALYST 9000 SWITCH POWER SUPPLY

C9400-PWR-3200ACT

3200W AC PSU · Catalyst 9400 · Titanium Rated

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9400-PWR-3200ACT
Category	Catalyst 9000 Switch Power Supply
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9000 SWITCH POWER SUPPLY

C9400-PWR-3200ACT

3200W AC PSU · Catalyst 9400 · Titanium Rated

C9400-PWR-3200ACT is a Cisco Catalyst 9400 Series 3200W AC Titanium-rated power supply for Catalyst 9400 modular switch chassis. It serves as a spare or build-time PSU for chassis power bays that require the ACT power-supply family, with single-phase AC input, 1570W output at 100-120 VAC or 3200W output at 200-240 VAC, a C19 appliance connector, and a listed 19.87 CFM minimum airflow requirement at full load.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	C9400-PWR-3200ACT	Cisco ordering PID	C9400-PWR-3200ACT (=)
Product type	3200W AC Titanium-rated power supply module	Cisco ordering description	Cisco Catalyst 9400 Series Titanium Rated 3200W AC Power Supply
Compatible platform	Cisco Catalyst 9400 Series modular switch chassis	Input type	Single-phase AC
AC-input type	Wide-ranging input with power factor correction	AC input voltage	85 to 132 VAC low-line or 180 to 264 VAC high-line
AC input current	17.6 A at 100 VAC or 200 VAC	AC input frequency	50/60 Hz nominal, 47 to 63 Hz full range
Branch circuit requirement	Dedicated fused branch circuit; North America 20A	Total output power	1570W at 100-120 VAC or 3200W at 200-240 VAC
55 VDC output capacity	1560W at 115 VAC or 3190W at 230 VAC	3.3 VDC standby output	10W
Low-line output current	28.36 A at 55V; 3.0 A at 3.3V	High-line output current	58 A at 55V; 3.0 A at 3.3V
Output holdup time	20 ms minimum	Minimum airflow	19.87 CFM at 100 percent load with a single fan
Heat dissipation	948.87 BTU/hr at 3200W; 465.54 BTU/hr at 1570W	Weight	4.0 to 5.0 lb (1.81 kg to 2.3 kg)
Power cord connector	IEC60320/C19 appliance connector	Power supply modes	Redundant and combined modes
Release support	Cisco IOS XE 17.13.1 hardware support	RFID tag	Front-facing passive UHF RFID tag

Get Price and Availability for C9400-PWR-3200ACT

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH