


CISCO · CATALYST 9400 SWITCHES

C9410R

8 Line Card Slots · Up To 384 Access Ports · 4320W PoE Budget Per Slot

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9410R
Category	Catalyst 9400 Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9400 SWITCHES

C9410R

8 Line Card Slots · Up To 384 Access Ports · 4320W PoE Budget Per Slot

The C9410R is the Cisco Catalyst 9400 Series 10 slot chassis and the density ceiling of the family, holding eight line cards in slots 1 to 4 and 7 to 10 while slots 5 and 6 stay reserved for a redundant supervisor pair.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C9410R	Cisco ordering description	Cisco Catalyst 9400 Series 10 slot chassis, spare part number C9410R=
Total slots	10	Line-card slots	8, in slot positions 1 to 4 and 7 to 10
Supervisor engine slots	2, in dedicated slot positions 5 and 6	Slot restriction	Line cards are not supported in the supervisor engine slots
Supervisor engines supported	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP-1XL-Y, C9400X-SUP-2 and C9400X-SUP-2XL	Supervisor engine redundancy	Yes, 1+1 redundancy with NSF/SSO and ISSU under 200 msec on dual supervisor engines
Bandwidth per line-card slot	480 Gbps with C9400X-SUP-2XL, 240 Gbps with C9400X-SUP-2, 80 Gbps with C9400-SUP-1XL, C9400-SUP-1XL-Y and C9400-SUP-1	Maximum bandwidth scalability per line-card slot	Up to 480 Gbps on all slots
Maximum 1G copper ports	384 ports of 10/100/1000BASE-T RJ-45, including PoE+ and UPOE variants	Maximum multigigabit ports	384 ports of 5G multigigabit and 384 ports of 10G multigigabit
Maximum fiber ports	384 ports of 1G SFP and 384 ports of 10G SFP+	Maximum 802.3bt Type 4 ports	384 ports at 90W, with 260 ports able to supply full 90W concurrently at max power
Maximum 25G ports	168 ports of SFP28, requires C9400X-SUP-2 or C9400X-SUP-2XL	Maximum 40G and 100G ports	96 ports of QSFP+ and 32 ports of QSFP28, both requiring C9400X-SUP-2 or C9400X-SUP-2XL
Integrated PoE	Yes	PoE standards	IEEE 802.3af, IEEE 802.3at and the Cisco pre-standard power implementation
PoE power budget per line-card slot	4320W with current shipping line cards	Maximum PoE capability per slot	Approximately 4800W chassis capability
Power supply bays	8	Power supply configuration	C9400-PWR-3200ACT and C9400-PWR-3200AC 3200W AC, C9400-PWR-2100AC 2100W AC, C9400-PWR-3200DC 3200W DC, ordered as separate line items
Power supply modes	Redundant N+N, redundant N+1 and combined mode, with AC or DC supplies in every mode	Combined mode formula	Total combined mode power equals P plus (N-1) x P x share ratio, where P is the output of one supply unit
AC input voltage	100 to 240 VAC with plus or minus 10 percent for full range	DC input voltage	-48 to -60 VDC with +20/-16.6 percent for full range
3200W AC supply rated input	16A at 100 VAC and 16A at 200 VAC	2100W AC supply rated input	10.4A at 100 VAC and 10.4A at 200 VAC

3200W DC supply rated input	36A per input, 72A total	Supply data output	3.3V at 3.0A on all three supplies, with 55V rails at 58.0A on the 3200W units and 38.21A on the 2100W unit at 230VAC
Heat dissipation	950 BTU/hr per 3200W AC or DC supply and 460 BTU/hr per 2100W AC supply	Holdup time	20 ms on the AC supplies and 8 ms on the DC supply
Power supply serviceability	Hot swappable, with per-unit Output Fail red LED, Input Okay green LED and blue ID LED	Power supply MTBF	300,000 hours on the 3200W AC, 2100W AC and 3200W DC units
Power supply minimum software	Cisco IOS XE 16.6.1 for the 3200W AC unit, 16.8.1 for the 2100W AC unit and 16.9.1 for the 3200W DC unit	Fan tray	One fan-tray bay with the C9410-FAN dual serviceable fan tray
Dimensions (H x W x D)	22.61 x 17.30 x 16.30 in. (57.43 x 43.94 x 41.40 cm)	Rack units	13 RU
Chassis weight	65.0 lb (29.48 kg) with fan tray	Mounting	19-in rack compatible from the front, with 19-in rack and cable guide hardware included
Operating temperature	23 to 113 degrees F (-5 to +45 degrees C) up to 6,000 feet and 23 to 104 degrees F (-5 to +40 degrees C) up to 10,000 feet, with 0 degrees C minimum ambient for cold startup	Short-term exceptional conditions	23 to 131 degrees F (-5 to +55 degrees C) up to 6,000 feet and 23 to 122 degrees F (-5 to +50 degrees C) up to 10,000 feet
Storage temperature	-40 to 158 degrees F (-40 to 70 degrees C)	Relative humidity	10 to 95 percent, noncondensing
Operating altitude	-60 to 3000m	Asset tracking	Embedded RFID tags on the chassis, supervisor, line cards, power supplies and fan trays
Minimum software release	Cisco IOS XE 16.6.1 with C9400-SUP-1, 16.6.2 with C9400-SUP-1XL, 16.9.1 with C9400-SUP-1XL-Y, and 17.7.1 with C9400X-SUP-2 or C9400X-SUP-2XL	Rated MTBF	1,404,840 hours
Safety certifications	UL 60950-1, CAN/CSA-C222.2 No. 60950-1, EN 60950-1, IEC 60950-1, AS/NZS 60950.1 and IEEE 802.3, with CE Marking	EMC certifications	47 CFR Part 15, CISPR22 Class A, KN 32 Class A, EN 300 386 V1.6.1, EN 55022 Class A, EN 55032 Class A, CISPR 32 Class A, EN61000-3-2, EN61000-3-3, ICES-003 Class A, TCVN 7189 Class A, V-3 Class A, CNS13438 Class A, CISPR24, EN55024, TCVN 7317 and KN35
Industry environmental standards	NEBS operating temperature -5 to 55C, relative humidity 10 to 93 percent, operating altitude up to 1829 m (6000 ft) at 55C, and ETSI 300-019 requirements	Chassis accessory part numbers	C9410-FAN=, C9410-ACC-KIT=, C9410-RACK-19-KIT=, C9410-SHELF-KIT=, C9400-S-BLANK= and C9400-PWR-BLANK=

Optional Add-ons

Add-on	Cisco PID	Purpose
Network Module	C9400-LC-48H	48x 10/100/1000 RJ-45 UPOE+ Ports - 90W Per Port - Catalyst 9400 Line Card
Network Module	C9400-LC-48P	48x1G RJ-45 - PoE+ 30W - Catalyst 9400 Line Card
Network Module	C9400-LC-48T	48x1G RJ-45 - Data Only - Catalyst 9400 Line Card

Network Module	C9400-LC-48U	48x1G RJ-45 - Cisco UPOE 60W - Catalyst 9400 Line Card
Network Module	C9400-LC-12QC	12x 40G QSFP+ or 4x 100G QSFP28 Ports - Supervisor 2 Required - Cat
Network Module	C9400-LC-24XS	24x 10G SFP+ or 1G SFP Ports - All Supervisors - Catalyst 9400 Line
Network Module	C9400-LC-24XY	20x 25G SFP28 + 4x 10G SFP+ Ports - Supervisor 2 Required - Cat
Network Module	C9400-LC-48S	48x 1G SFP Fiber Ports - Nonblocking - Catalyst 9400 Line Card
Power Supply / Fan	C9400-PWR-3200AC	3200W AC PSU - Catalyst 9400 - Platinum
Power Supply / Fan	C9400-PWR-2100AC	2100W AC PSU - Catalyst 9400 - Platinum Rated
Power Supply / Fan	C9400-PWR-3200DC	3200W DC Power Supply - Catalyst 9400

Get Price and Availability for C9410R

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00253253253253253253) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.