

CISCO · CATALYST 9000 SWITCH POWER SUPPLY

C9K-PWR-930WDC-R

930W DC PSU · Catalyst 9500 High Performance

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	C9K-PWR-930WDC-R
Category	Catalyst 9000 Switch Power Supply
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9000 SWITCH POWER SUPPLY

C9K-PWR-930WDC-R

930W DC PSU · Catalyst 9500 High Performance

C9K-PWR-930WDC-R is a Cisco Catalyst 9500 Series High Performance 930W DC power supply module for the C9500-32QC, C9500-48Y4C, and C9500-24Y4C switches, used when those platforms need a like-for-like DC replacement or a DC power option in a dual-supply chassis.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	C9K-PWR-930WDC-R	Product type	DC power supply module
Cisco ordering description	930W DC Power Supply	Compatible switch models	C9500-32QC, C9500-48Y4C, C9500-24Y4C
Power supply slots	Two AC or DC power supply slots	FRU support	Field-replaceable and hot-swappable power supply module
Supported PSU combinations	Two AC, two DC, AC-DC, or one installed PSU with blank cover in unused slot	Power max rating	930W
Input voltage range	DC -40 to -72 VDC	Input current	DC 23A max at -48VDC when fully loaded
Power supply efficiency	92 percent typical	Output ratings	12V main at 54A; 12V standby at 3A
Output holdup time	8 ms minimum for system	Input receptacle	Molex Minifit 44540-1001
Power cord rating	DC 40A	BTU with C9500-32QC	1,856 BTU/hr
BTU with C9500-48Y4C	1,856 BTU/hr	BTU with C9500-24Y4C	1,484 BTU/hr
MTBF	3,008,280 hours	PSU hardware features	Power cord retainer, release handle, PSU fan, DC+ connector, DC- connector, and release latch
LED status support	Green power status and amber power supply failure LEDs	DC cable preparation	Strip 0.75 in. (19 mm) from unstripped cable ends before connection
DC terminal mapping	Negative cable to negative terminal and positive cable to positive terminal of the same DC source	Redundant ordering option	C9K-PWR-930WDC-R/2
Blank-cover requirement	Unused power supply slot must retain the required blank cover		

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[View Product Page](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.