

CISCO PHONE

CP-8832-K9

Conference Phone · North America Charcoal Base · Enhanced UCL

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CP-8832-K9
Category	Cisco Phone
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO PHONE

CP-8832-K9

Conference Phone · North America Charcoal Base · Enhanced UCL

CP-8832-K9 is the Cisco IP Conference Phone 8832 charcoal base for North America, an IP conference phone endpoint for medium to large meeting rooms that register to Cisco Unified Communications Manager.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CP-8832-K9	Product type	IP conference phone
Color	Charcoal	Regional scope	North America
Included package	Adapter with 9.8-ft (3-m) USB-C cable	Base room coverage	20 x 20 ft room with up to 10 participants
Expanded room coverage	20 x 57 ft with two 8832 bases, daisy-chain kit, and wireless microphones	Display	480 x 128 pixel backlit 24-bit color LCD, 3.9 in. diagonal
Ethernet interface	10/100BASE-T via Ethernet injector	PoE class	IEEE PoE Class 3
PoE compatibility	IEEE 802.3af and IEEE 802.3at switch blades	Wired power option	Cisco IP Conference Phone 8832 PoE Adapter or non-PoE Ethernet Adapter
Wi-Fi power option	Cisco IP Conference Phone 8832 Power Adapter	CUCM license	Enhanced User Connect License
Call control support	Native support in Cisco Unified Communications Manager 12.0(1)	DevPack support	DevPack required for Cisco Unified Communications Manager 10.5.2, 11.0, and 11.5
Signaling protocol	Session Initiation Protocol	Network protocols	IPv4, IPv6, DHCP, DNS, TFTP, HTTPS, VLAN, RTP, RTCP, CDP, and LLDP
Audio codec support	G.711, G.722, G.729a, G.729ab, iLBC, and OPUS	Wireless extension microphones	Supported on Cisco IP Conference Phone 8832
No-radio alternative	CP-8832-NR-K9 does not support Wi-Fi, wireless expansion microphones, or Bluetooth	Daisy-chain kit	Two 8832 base units require CP-8832-DC= for North America
Operating temperature	32 to 104 degrees F (0 to 40 degrees C)	Operating humidity	10% to 90%, noncondensing
Dimensions	10.9 x 10.9 x 2.4 in. (278 x 278 x 61.3 mm)	Weight	4.07 lb (1852 g)

Get Price and Availability for CP-8832-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3070-23switch) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH