

CISCO PHONE

CP-8851-K9

5-Line IP Phone · USB and Bluetooth · Enhanced UCL

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CP-8851-K9
Category	Cisco Phone
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO PHONE

CP-8851-K9

5-Line IP Phone · USB and Bluetooth · Enhanced UCL

The CP-8851-K9 is a Cisco IP Phone 8800 Series desk phone for attendant and shared-line desks that add Key Expansion Modules. The phone has five programmable line and feature keys, a 5-inch 800 x 480 color display, a two-port Gigabit Ethernet switch and a side USB port, and it supports Bluetooth 3.0 EDR Class 1.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CP-8851-K9	Product type	Cisco IP Phone 8851 desk phone
CUCM license	Enhanced User Connect License	Key expansion module support	Up to two Cisco IP Phone 8800 KEMs
CUCM support	Cisco Unified Communications Manager 12.5 and later	Unified CME support	10.0 and later through fast track
BE 6000 support	8.6.2, 9.1.2, 10.5.2, 11.0 and later	HCS support	8.6.2 and later using supported UCM versions
Codec support	G.711, G.722, G.722.2, G.729ab, iLBC, iSAC, OPUS	Security slot	Kensington Security Slot compatible
Cisco ordering ID	CP-8851-K9=	Color	Charcoal
Same-model color SKU	CP-8851-W-K9= is Cisco IP Phone 8851, White	No-radio comparison SKU	CP-8851NR-K9= is Cisco IP Phone 8851NR, Charcoal
Programmable keys	5	Display	5 in. 800 x 480 24-bit color WVGA display
Bluetooth	Bluetooth 3.0 EDR Class 1 up to 66 ft (20 m)	Bluetooth profiles	Hands-Free Profile and Phone Book Access Profile
Mobile integration	Cisco Intelligent Proximity audio path, call history, and contact synchronization	Ethernet switch	Internal 2-port 10/100/1000BASE-T Cisco Ethernet switch
PC connectivity	Single LAN connection for phone and co-located PC	Expansion button range	From 5 or 10 line buttons to 61 or 66 line buttons with KEMs
Signaling protocol	Session Initiation Protocol	Discovery protocols	Cisco Discovery Protocol, LLDP-MED
Switch speed	Auto-negotiation	Headset control	Electronic hookswitch through USB, auxiliary port, or Bluetooth pairing
Foot-stand positions	35 degrees and 50 degrees	Phone casing composition	Polycarbonate ABS textured plastic
Bezel	Black bezel included, optional silver bezel orderable separately	QoS	802.1Q/p
USB	Side USB port with up to 500 mA at 5V output	Power input rating	0.917A, 48V DC
Local power option	Cisco IP Phone Power Cube 4 with corresponding AC country cord	PoE class	IEEE PoE Class 3 before hardware V08 and Class 4 for hardware V08 and above

PoE standards	Compatible with IEEE 802.3af and IEEE 802.3at switch blades	Dimensions	9.02 x 10.13 x 1.57 in. excluding foot stand
Wall mounting	Optional wall-mount kit available separately	Operating temperature	0°C to 40°C (32°F to 104°F)
Operating humidity	10% to 90%, noncondensing		

Get Price and Availability for CP-8851-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.