Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-BAR-T-K9

12MP Camera 120-Degree View · Table Room Navigator · Cisco Room Bar

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock

Product Model	CS-BAR-T-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty

CISCO VIDEO CONFERENCING

CS-BAR-T-K9

12MP Camera 120-Degree View · Table Room Navigator · Cisco Room Bar

The CS-BAR-T-K9 is the Cisco Room Bar in First Light color ordered together with a table-stand Room Navigator, carrying compliance model TTC7-28.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-BAR-T-K9	**Cisco ordering description**	Cisco Room Bar (First Light Color) with table-stand Room Navigator
Compliance model number	TTC7-28	**Default box components**	Cisco Room Bar and Cisco Room Navigator in table-stand form
Camera	12MP at 30 fps on 1/2.3 in CMOS with fixed focus lens and 5x digital zoom	**Camera field of view**	120 degrees horizontal and 95 degrees vertical at f/2.5
Camera intelligence	Auto framing with face detect, speaker tracking, automatic brightness and white balance, Frames camera mode, automatic image rotation when inverted	**Video standards**	H.263, H.264 and AV1
Video inputs	One HDMI and one USB-C, both up to 3840 x 2160 at 30 fps including 1920 x 1080 at 60 fps, with CEC 2.0	**Video outputs**	Two HDMI up to 3840 x 2160 at 60 fps with CEC 2.0 and touchscreen support over USB-A touch signaling
Encode and decode	Video stream 1920 x 1080 at 30 fps and content stream 3840 x 2160 at 15 fps	**Bandwidth**	Up to 20 Mbps
Audio standards	G.711, G.722, G.722.1, G.729, AAC-LD and Opus	**Audio features**	Acoustic echo cancellation, active lip synchronization, AI-powered noise removal, automatic gain control, beamforming microphones, de-reverberation, full duplex, full-band audio, Self-Hear, Spatial Audio and Ultrasound Technology
Microphone array	4-element beamforming array with additional front-facing microphones for speaker tracking	**Loudspeaker system**	Stereo pair of two full-range drivers with directional audio, 100 Hz to 20 kHz response and 93 dB maximum SPL
Audio inputs	One HDMI, one analog microphone input, one DisplayPort/USB-C, one USB-A, Bluetooth on radio versions and one PoE port for audio over IP with a single Cisco IP microphone	**Audio outputs**	One DisplayPort/USB-C, one USB-A and Bluetooth on radio versions
Published room coverage	Internal array optimized for up to five people seated within 3 meters; external microphone recommended beyond that	**Network interface**	One Ethernet RJ-45 100/1000 Mbps for LAN plus one Ethernet RJ-45 100/1000 Mbps PoE port for Room Navigator pairing
Wireless	Wi-Fi 802.11a/b/g/n/ac on 2.4 GHz and 5 GHz with 2x2 MIMO	**USB-C passthrough**	Camera, microphone and speakers over one USB-C cable with content sharing and display extension at 3840 x 2160 at 30 fps

LAYER23 SWITCH

Other interfaces	Bluetooth and Bluetooth Low Energy, one USB 2.0 type A port, one micro-USB service port and a factory reset pinhole	**Wireless sharing**	Webex app up to 3840 x 2160 at 7.5 fps, Miracast at 1920 x 1080 at 60 fps, Apple AirPlay and Microsoft Teams Cast on Microsoft Teams Rooms
Firewall traversal	Cisco Expressway technology with H.460.18 and H.460.19	**Certificate management**	Manufacturer Installed Certificate signed by Cisco for CAPF onboarding to Cisco UCM, plus user-installed certificates for IEEE802.1x, Wi-Fi, HTTPS and SIP-TLS
Power input	100 to 240 VAC at 50/60 Hz with 12V DC input, peak 86W	**Power consumption**	14.3W in an active meeting, 8.2W idle and 7W networked standby
Required power supply	PSU-12VDC-86W, spare part number PSU-12VDC-86W=	**Software compatibility**	RoomOS 11 or later with interoperability for Microsoft Teams, Zoom and Google Meet
Main unit dimensions	21 x 3.2 x 2.5 in (53.4 x 8.2 x 6.4 cm) at 3.3 lb (1.5 kg)	**Packaged dimensions**	23.9 x 9.8 x 7.2 in (60.7 x 24.9 x 18.3 cm) at 11.5 lb (5.2 kg) with the table-stand Room Navigator
Mounting	Consolidated mounting unit for walls and screens with gap bar, mounted above or beneath the displays and invertible with a separately flipped speaker grille	**Operating temperature**	0 to 35 degrees C at 10% to 90% relative humidity
Storage and transport	-20 to 60 degrees C at 10% to 90% RH noncondensing	**Approvals and compliance**	Directive 2014/53/EU for radio versions and Directives 2014/30/EU and 2014/35/EU for non-radio versions

Get Price and Availability for CS-BAR-T-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch
Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23 SWITCH