

CISCO VIDEO CONFERENCING

CS-BARPRO-C-K9

Dual 48MP Camera System · Carbon Black · Cisco Room Bar Pro

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CS-BARPRO-C-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO VIDEO CONFERENCING

CS-BARPRO-C-K9

Dual 48MP Camera System · Carbon Black · Cisco Room Bar Pro

The CS-BARPRO-C-K9 is the Carbon Black ordering finish of the Cisco Room Bar Pro, supplied with the Room Navigator table stand, mount and accessories at compliance model TTC4-01. Hardware matches the First Light bundle CS-BARPRO-K9 exactly; only the enclosure color changes.

New, factory-sealed · 3-year LSCare warranty · 14-day returns ·
Cisco SN check before shipment

Specifications

Product ID	CS-BARPRO-C-K9	Cisco ordering description	Cisco Room Bar Pro in Carbon Black with Room Navigator table stand, mount and accessories
Compliance model number	TTC4-01	Camera system	Dual camera with 112-degree wide-angle lens and 70-degree tele-lens, both on 48 MP image sensors
Camera sensor and rate	1/1.3 in Quad Bayer at 30 fps	Camera movement	Motorized tilt between -2 and 20 degrees
Camera zoom	5x digital zoom, rising to 10x with AI virtual lens enabled	Camera aperture	f/2.8 on the 112-degree lens and f/1.85 on the 70-degree lens
Camera field of view	112 and 70 degrees horizontal with 94 and 55 degrees vertical	Camera reach	Up to 4 m single-person frame and 7 m two-person frame, extended with virtual lens zoom
Camera intelligence	Auto framing with face detect, speaker tracking, automatic brightness and white balance, automatic image rotation when inverted	Camera focus	Fixed focus on the 112-degree lens and VCM auto focus on the 70-degree lens
Presenter tracking	Requires a Cisco PTZ 4K Camera connected over Ethernet and HDMI in, using AI face and upper-body detection within a defined zone	Video input	One HDMI up to 3840 x 2160 at 30 fps including 1920 x 1080 at 60 fps
Video outputs	Three HDMI outputs up to 3840 x 2160 at 60 fps	Loudspeaker system	3-channel set of three full-range drivers plus a mechanically balanced dual woofer section with directional audio
Loudspeaker response	70 Hz to 22 kHz with 97 dB maximum sound pressure level	Microphone array	16-element beamforming array with 120 Hz to 16 kHz response
Published room coverage	Optimized for small to medium rooms with people seated within 4 meters; speaker tracking rated to 6 meters	Network interface	One Ethernet RJ-45 10/100/1000 Mbps for LAN
PoE ports	One 802.3af port at 15.4W for Room Navigator pairing plus two 802.3af ports at 15.4W each for AV over IP peripherals and Cisco or third-party audio equipment	Wireless	Wi-Fi 802.11a/b/g/n/ac/ax on 2.4, 5 and 6 GHz with 2x2 MIMO and Wi-Fi 6E tri-band; absent on non-radio versions
USB-C passthrough	Camera, microphone and speakers over one USB-C cable at up to 3840 x 2160 at 30 fps with content sharing on the same cable	Other interfaces	Bluetooth and Bluetooth Low Energy absent on non-radio versions, plus two USB 2.0 type A ports
Power input	100 to 240 VAC at 50/60 Hz from a built-in power supply	Power consumption	Average 20W, 12.7W networked standby and 1W standby

Power control	Power button on the top of the bar with configurable office hours mode forcing standby outside preset hours	Main unit dimensions	37.8 x 4.3 x 3.5 in (96 x 11 x 9 cm) at 9.86 lb (4.47 kg)
Packaged dimensions	44.3 x 9.2 x 8.9 in (112.6 x 23.3 x 22.7 cm) at 19.6 lb (8.9 kg) with the table-stand Room Navigator	Mounting	Consolidated mounting unit for walls and displays with gap bar, mounted above or beneath the screens and invertible with a de-attachable flipped speaker grille
Software compatibility	RoomOS 11.5.1.x or later with interoperability for Microsoft Teams, Zoom and Google Meet; on-premises deployments from RoomOS 11.5.2.x	Operating temperature	0 to 35 degrees C at 10% to 90% relative humidity
Storage and transport	-20 to 60 degrees C at 10% to 90% RH noncondensing	Accessory part numbers	CS-BARPRO-MOUNT= wall and screen mounting kit spare and CS-BARPRO-CAMCOV= privacy camera cover spare
Approvals and compliance	Directive 2014/53/EU for radio versions and Directives 2014/30/EU and 2014/35/EU for non-radio versions		

Get Price and Availability for CS-BARPRO-C-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)[View Product Page](#)

Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23 switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.