Layer23 switch.com

PRODUCT DATASHEET
Revised October 2026

CISCO VIDEO CONFERENCING

CS-KIT-EQ-C-K9

Carbon Black Quad Camera · Codec EQ Bundle · Cisco Room Kit EQ

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock

Product Model	CS-KIT-EQ-C-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com

Scan for price and stock

200+	18,000+	US$9M+	3-Year
Countries Served	Customers Worldwide	Ready-Stock Inventory	Warranty

CISCO VIDEO CONFERENCING

CS-KIT-EQ-C-K9

Carbon Black Quad Camera · Codec EQ Bundle · Cisco Room Kit EQ

The CS-KIT-EQ-C-K9 is the Carbon Black ordering finish of the Cisco Room Kit EQ, a large-room collaboration bundle made up of the CS-CODEC-EQ-K9 Codec EQ, the Carbon Black CS-QUADCAM2-C Quad Camera and the CS-T10-TS-L Room Navigator for Table.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-KIT-EQ-C-K9	**Cisco ordering description**	Cisco Room Kit EQ - Carbon Black
Bundle scope	CS-CODEC-EQ-K9 Codec EQ, CS-QUADCAM2-C Carbon Black Quad Camera and CS-T10-TS-L Room Navigator for Table	**Compliance model numbers**	TTC6-15, TTC8-10 and TTC5-15
Camera sensors	Four CMOS image sensors with machine intelligent switching at up to 20MP per sensor, combined into a single 1080p output	**Camera optics**	7x zoom from 5x native optical zoom with digital enhancement, f/2.0 aperture, 1/1.7 CMOS
Camera field of view	83 degrees horizontal on the wide lens and 50 degrees horizontal on the three tele-lenses	**Camera resolution**	5056 x 3888 pixels
Camera intelligence	Automatic group framing with audio and face detect, speaker tracking, Frames camera mode and meeting zones	**Camera focus**	Automatic focus, brightness and white balance with focus distance 1 m to infinity, up to 60 fps
Camera control	Ethernet (LAN)	**Video standards**	H.264, H.265, H.263 and AV1
Video inputs	One USB-C up to 3840 x 2160 at 30 fps, three HDMI up to 3840 x 2160 at 30 fps including 1920 x 1080 at 60 fps with HDCP 1.4 on one input, and four PoE++ 1 Gb Ethernet ports for video over IP	**Video over IP capacity**	Up to three streams at 1920 x 1080 at 60 fps or one stream at 3840 x 2160 at 30 fps
Video outputs	Three HDMI outputs up to 3840 x 2160 at 60 fps with CEC 2.0 and interactive touch screen support over HDMI out plus USB-A	**Encode and decode**	Main video 1920 x 1080 at 60 fps and presentation channel 3840 x 2160 at 15 fps
USB passthrough	One USB 3.2 gen1 at up to 5 Gbps carrying camera, microphone and speakers over a single USB-C cable	**Bandwidth**	Up to 20 Mbps, with 1472 kbps minimum for 1080p30 and 2560 kbps for 1080p60
Audio standards	G.711, G.722, G.722.1, G.729, AAC-LD and Opus	**Audio features**	20 kHz full-band audio, acoustic echo cancellation, active lip synchronization, AI-powered adaptive noise removal, automatic gain control, full duplex, Self-Hear and Ultrasound Technology
Audio inputs	Three mini jack analog, three HDMI, one USB-C, one USB-A, four PoE++ Ethernet for audio over IP, up to eight Cisco IP microphones and AES67 third-party systems with the AV Integrator License	**Audio outputs**	One analog line out, three HDMI audio outputs, one USB-A, one USB-C and four PoE++ Ethernet for audio over IP

LAYER23-SWITCH

Loudspeakers	Quad Camera loudspeaker system with a single full-range driver and dual low-frequency drivers	**Network interface**	One Ethernet RJ-45 10/100/1000 for LAN plus four PoE++ 802.3bt RJ-45 10/100/1000 ports
PoE++ power budget	Up to 90W total across the four 802.3bt ports for camera, Room Navigator and AV over IP peripherals	**Wireless**	Wi-Fi 802.11a/b/g/n/ac/ax on 2.4 GHz, 5 GHz and 6 GHz with 2x2 MIMO; Wi-Fi 6E absent in non-radio versions
Other interfaces	Four USB-A 3.0 ports at up to 1.5A charging each, Bluetooth and Bluetooth Low Energy absent in non-radio versions, Micro USB service port and factory reset pinhole	**Call control**	Native CUCM registration requiring version 12.5 or later with the Room Kit EQ device pack, native Cisco Expressway registration, Webex, third-party H.323 gatekeepers and SIP proxies
Firewall traversal	Cisco Expressway technology with H.460.18 and H.460.19	**Wireless sharing**	Webex App up to 3840 x 2160 at 7.5 fps including 1920 x 1080 at 30 fps, Miracast and Apple AirPlay
Network diagnostics	Network-level diagnostics and observability with Cisco ThousandEyes integration	**Power input**	100 to 240 VAC at 50/60 Hz
Power consumption	18W in an active meeting, 18W idle and 15W with display off in standby	**Camera power supply**	Quad Camera must be used with PSU-12VDC-70W-GR=
Operating temperature	0 to 35 degrees C for Quad Camera; 0 to 40 degrees C for Room Navigator and Codec EQ	**Operating humidity**	10% to 90% relative humidity
Storage and transport	-20 to 60 degrees C at 10% to 90% RH noncondensing	**Quad Camera dimensions**	37.4 x 4.7 x 4.0 in (95.0 x 12.0 x 10.3 cm) at 10.6 lb (4.8 kg)
Codec EQ dimensions	18.6 x 1.7 x 8 in (47.3 x 4.4 x 20.2 cm) at 5.1 lb (2.33 kg)	**Mounting**	Quad Camera above or beneath the screens or wall mounted; Codec EQ wall mounted, rack eared or free-standing
Camera color options	First Light and Carbon Black	**Locking mechanism**	Kensington security lock on the Codec EQ
Advanced audio unlock	Full Audio API and Audio Console with the AV Integrator option key, also required for AES67	**Accessory part numbers**	CS-CODEC-EQ-ANT=, PSU-12VDC-70W-GR=, CAB-ETH-1.5M-GR, CAB-ETH-3M-GR, CAB-ETH-5M-GR, CAB-CAT5E-4M, CAB-CAT5E-8M, CAB-CAT5E-12M, CAB-CAT5E-CMP-20M and CAB-CAT5E-CMP-30M
Approvals and compliance	Directive 2014/53/EU for radio versions, Directives 2014/30/EU and 2014/35/EU for non-radio versions, RoHS 2011/65/EU, WEEE 2002/96/EU and NRTL product safety		

Get Price and Availability for CS-KIT-EQ-C-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

Request a Quote

View Product Page

Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch
Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.