

CISCO VIDEO CONFERENCING

CS-KIT-MINI-K9

4K Camera 120-Degree View · USB Passthrough · Cisco Room Kit Mini

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CS-KIT-MINI-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO VIDEO CONFERENCING

CS-KIT-MINI-K9

4K Camera 120-Degree View · USB Passthrough · Cisco Room Kit Mini

The CS-KIT-MINI-K9 is the Webex Room Kit Mini upfront pricing bundle, pairing the Room Kit Mini unit with a Webex Room Navigator under component part numbers CS-KIT-MINI and CS-T10-TS at compliance models TTC7-26 and TTC5-15. It is an all-in-one huddle-room video system that folds camera, microphones, speakers and codec into a 19.7-inch bar weighing 4 lb.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	CS-KIT-MINI-K9	Bundle scope	Webex Room Kit Mini unit CS-KIT-MINI and Webex Room Navigator CS-T10-TS
Compliance model numbers	TTC7-26 and TTC5-15	Camera	4K UltraHD supporting up to 30 fps with 8 MP image sensor on 1/2.5 in CMOS
Camera optics	5x zoom at f/1.4 with 120 degrees horizontal field of view	Camera intelligence	Auto framing with face detect and best overview
Video standard	H.264	Video input	One HDMI up to 3840 x 2160 at 30 fps including HD1080p60 with CEC 2.0
Video output	One HDMI up to 3840 x 2160 at 60 fps with CEC 2.0	Encode and decode	Live video up to 1920 x 1080 at 30 and 60 fps
Audio standards	G.711, G.722, G.722.1, G.729, AAC-LD and Opus	Audio features	High-quality 20 kHz audio, automatic gain control, automatic noise reduction and active lip synchronization
Audio inputs	One audio in from HDMI, internal microphones and Bluetooth on radio versions	Integrated speakers	Full range speaker plus dual woofers in balanced configuration at 100 Hz to 20 kHz, 24W amplifier power and 84 dB maximum SPL
Network interface	One Ethernet RJ-45 10/100/1000 for LAN and one Ethernet RJ-45 for Cisco Touch 10 direct pairing	Wireless	Wi-Fi 802.11a/b/g/n/ac on 2.4 GHz and 5 GHz, absent in non-radio versions
USB passthrough	Joins any web conferencing service and shares content using the Room Kit Mini camera, microphones and speakers at 720p, with a USB cable to the external monitor and HDMI to the computer	Other interfaces	One USB 2.0 type A port
Bandwidth	Up to 6 Mbps point to point, with 1472 kbps minimum for 1080p30 and 2560 kbps for 1080p60	Firewall traversal	Cisco Expressway technology with H.460.18 and H.460.19
MultiSite	H.239 H.323 dual stream	Software compatibility	Cisco Collaboration Endpoint Software Version 9.14.5 or later and Cisco Webex RoomOS
Power input	100 to 240 VAC at 50/60 Hz with 12V DC input	Power supply part number	PSU-12VDC-70W-GR=
Optional hardware	8 m HDMI presentation cable, 4 m USB cable for USB passthrough and Screen Mount Kit	Main unit dimensions	19.7 x 3.2 x 3 in (50.0 x 8.1 x 7.7 cm) at 4 lb (2 kg)

[View Product Page](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.