

CISCO VIDEO CONFERENCING

CS-KITPRO-K9

Codec Pro and Quad Camera · 8 Phantom Mic Inputs · Cisco Room Kit Pro

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CS-KITPRO-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO VIDEO CONFERENCING

CS-KITPRO-K9

Codec Pro and Quad Camera · 8 Phantom Mic Inputs · Cisco Room Kit Pro

The CS-KITPRO-K9 is the Cisco Room Kit Pro, an integrator-oriented large-room bundle of three ordered components: the CS-CODEC-PRO Codec Pro, the CS-QUADCAM Quad Camera and the CS-T10-TS-L Room Navigator on a table stand, carrying compliance models TTC6-13, TTC8-10 and TTC5-15.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-KITPRO-K9	Bundle scope	CS-CODEC-PRO Codec Pro, CS-QUADCAM Quad Camera and CS-T10-TS-L Room Navigator table stand
Compliance model numbers	TTC6-13, TTC8-10 and TTC5-15	Camera sensors	Four 20MP CMOS image sensors with machine intelligent switching into a single 1080p HD output
Camera rate and sensor	Up to 60 fps on 1/1.7 CMOS at 5056 x 3888 pixel resolution	Camera optics	5x zoom at f/2.0 with 83 degrees horizontal on the wide lens and 50 degrees horizontal on three tele-lenses
Camera intelligence	Automatic group framing with audio and face detect, speaker tracking, intelligent people framing, automatic focus, brightness and white balance	Video outputs	Two HDMI up to 3840 x 2160 at 60 fps and one HDMI up to 3840 x 2160 at 30 fps, all with CEC 2.0
Analog audio inputs	Eight 48V phantom powered microphone inputs on Euroblock connectors, each with separate echo cancelers and noise reduction and each settable to balanced line level	Digital audio inputs	Three HDMI digital stereo inputs and two USB-A digital stereo inputs
IP audio inputs	Up to eight Cisco IP microphones over PoE for directional voice pickup, which may require an external PoE switch	Third-party audio	Connectivity with third-party audio systems over AES67
Loudspeakers	Quad Camera loudspeaker system with a single full-range driver and dual low-frequency drivers	Network interface	One Ethernet RJ-45 10/100/1000 for LAN, two for direct camera pairing and control, and two with PoE for Room Navigator and IP room peripherals
Wireless	Wi-Fi 802.11a/b/g/n/ac on 2.4 GHz and 5 GHz at 2x2 MIMO, absent in non-radio versions	Bandwidth	Up to 20 Mbps
Call control	Cisco Collaboration Cloud and Webex	Software compatibility	RoomOS 10.x or later with Microsoft Teams over VIMT and WebRTC, Zoom over SIP, Google Meet over WebRTC, plus Microsoft Teams Rooms on Android
Camera power	100 to 240 VAC at 50/60 Hz with 12V DC input, adapter PSU-12VDC-70W-GR supplied in Quad Camera bundles	Camera power spare	PSU-12VDC-70W-GR=
Codec Pro dimensions	17.1 x 2.6 x 9.1 in (43.6 x 6.6 x 23.1 cm) at 7.3 lb (3.3 kg)		

Get Price and Availability for CS-KITPRO-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3071189993) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH