

CISCO VIDEO CONFERENCING

CS-KITPRO-PTZ4K-K9

Codec Pro and PTZ 4K Camera · Motorized Pan and Tilt · Cisco Room Kit Pro

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	CS-KITPRO-PTZ4K-K9
Category	Cisco Video Conferencing
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO VIDEO CONFERENCING

CS-KITPRO-PTZ4K-K9

Codec Pro and PTZ 4K Camera · Motorized Pan and Tilt · Cisco Room Kit Pro

The CS-KITPRO-PTZ4K-K9 is the Cisco Room Kit Pro ordered with the PTZ 4K Camera instead of the fixed Quad Camera, bundling the CS-CODEC-PRO Codec Pro, the Cisco PTZ 4K Camera and the CS-T10-TS-L Room Navigator on a table stand.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	CS-KITPRO-PTZ4K-K9	Bundle scope	CS-CODEC-PRO Codec Pro, Cisco PTZ 4K Camera and CS-T10-TS-L Room Navigator table stand
Camera movement	Motorized pan of plus or minus 170 degrees and tilt of plus or minus 20 degrees	Camera field of view	70 degrees horizontal
Camera zoom	12x digital zoom	Camera aperture	F-value 2.0 to 3.8
Camera focus distance	1.0 m to infinity at the wide setting	Camera adjustment	Focus, white balance and brightness set manually or automatically
Camera control	Visca over IP through the LAN port	Camera video interface	HDMI 2.0
Camera power	12V at 3A or 100 to 120 and 200 to 240 VAC at 50/60 Hz, PoE+ compatible under IEEE802.3at	Supported camera power supplies	FSP040-RHAN3, Phihong POE29U-1AT(PL) or Microsemi PD-9001GR/AT/AC
Video outputs	Two HDMI up to 3840 x 2160 at 60 fps and one HDMI up to 3840 x 2160 at 30 fps, all with CEC 2.0	Analog audio inputs	Eight 48V phantom powered microphone inputs on Euroblock connectors, each with separate echo cancelers and noise reduction and each settable to balanced line level
Digital audio inputs	Three HDMI digital stereo inputs and two USB-A digital stereo inputs	IP audio inputs	Up to eight Cisco IP microphones over PoE, which may require an external PoE switch
Third-party audio	Connectivity with third-party audio systems over AES67	Network interface	One Ethernet RJ-45 10/100/1000 for LAN, two for direct camera pairing and control, and two with PoE for Room Navigator and IP room peripherals
Wireless	Wi-Fi 802.11a/b/g/n/ac on 2.4 GHz and 5 GHz at 2x2 MIMO, absent in non-radio versions	Bandwidth	Up to 20 Mbps
Call control	Cisco Collaboration Cloud and Webex	Software compatibility	RoomOS 10.x or later with Microsoft Teams over VIMT and WebRTC, Zoom over SIP, Google Meet over WebRTC, plus Microsoft Teams Rooms on Android
Codec Pro dimensions	17.1 x 2.6 x 9.1 in (43.6 x 6.6 x 23.1 cm) at 7.3 lb (3.3 kg)		

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[View Product Page](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.