

CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-24PESK9

24x32G FC Ports · 24x16G SW Optics · Enterprise Exhaust

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	DS-C9132T-24PESK9
Category	MDS 9100 Series Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-24PESK9

24x32G FC Ports · 24x16G SW Optics · Enterprise Exhaust

DS-C9132T-24PESK9 is a Cisco MDS 9132T 32-Gbps Fibre Channel SAN switch bundle for server-rack SAN access in Cisco MDS 9000 fabrics.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	DS-C9132T-24PESK9	Product compatibility	Cisco MDS 9000 Family
Product type	32G Fibre Channel SAN switch	Order configuration	Enterprise switch with 24 active ports, 24 x 16G SW optics, 4 fans, 2 power supplies, Enterprise license, and port-side exhaust airflow
Form factor	1RU fixed-switch form factor	Fibre Channel ports	16 SFP+ ports plus one 16-port SFP+ expansion slot
Active ports at order	24 active Fibre Channel ports	Maximum Fibre Channel ports	Up to 32 active Fibre Channel ports
Fibre Channel speed support	4, 8, 16, and 32 Gbps autosensing	Dedicated bandwidth per port	32 Gbps
Aggregate bandwidth	1024 Gbps full duplex	Port activation license	8-port On-Demand Activation license for 24-port configurations
Buffer credits	Up to 8300 buffer credits for a group of 16 ports	Default buffer credits per port	500 buffer credits per port
Maximum buffer credits for a single port	8270 buffer credits in the port group	Port channel support	Up to 16 load-balanced physical links in one port channel
Fibre Channel port types	E, F, and B standard port types; SD, ST, NP, and TE enhanced port types	NVMe/FC support	NVMe/FC listed by Cisco for the platform
Management Ethernet ports	Two out-of-band 10/100/1000 Ethernet management ports	Console port	RS-232 serial console port
USB port	USB power-on auto-provision port	Network management	Cisco Data Center Network Manager and standards-based SNMP management listed
Minimum NX-OS release	Cisco MDS NX-OS Release 8.2(1) or later	Minimum Cisco DCNM release	Cisco DCNM Release 10.4(1) or later
Network license	Enterprise license included in the DS-C9132T-24PESK9 order line	Enterprise license features	Inter-VSAN routing, QoS controls, Fibre Channel security functions, traffic encryption support, VSAN-based access control, and fabric binding listed
Fan modules	4 fan modules in the ordering description	Power supplies	2 power supplies in the ordering description
Default power supply	DS-CAC-650W-E 650W AC port-side exhaust power supply; two supplies in the order configuration	AC input voltage	100 to 240 VAC
AC input frequency	50 to 60 Hz nominal	Power supply output capacity	650W

Power supply output voltage	12V +/- 5 percent, up to 54A	Output hold-up time	20 ms
Maximum system power	180W	Heat dissipation	614 BTU/hr
Airflow direction	Back to front toward ports using port-side exhaust fans	System airflow rate	50 CFM through system fan assembly at 77F (25C)
Maximum airflow rate	100 CFM maximum	Dimensions	1.72 x 17.3 x 20.11 in. (4.37 x 43.94 x 51.08 cm)
Weight	21.65 lb (9.82 kg)	Operating temperature	32 to 104F (0 to 40C)
Nonoperating temperature	-40 to 158F (-40 to 70C)	Operating relative humidity	10 to 90 percent noncondensing
Nonoperating relative humidity	10 to 95 percent noncondensing	Operating altitude	-197 to 6500 ft (-60 to 2000 m)
Included FC optics	24 x Cisco 16G Fibre Channel shortwave optics	Supported FC optics	32G SW, 32G LW, 16G SW, 16G LW, 16G ELW, 8G SW, 8G LW, 8G ER, and 8G CWDM SFP+ optics

Get Price and Availability for DS-C9132T-24PESK9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00253333333333333333) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.