

CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-8PMESK9

8x32G FC Ports · 8x16G SW Optics · Exhaust SAN Switch

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	DS-C9132T-8PMESK9
Category	MDS 9100 Series Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-8PMESK9

8x32G FC Ports · 8x16G SW Optics · Exhaust SAN Switch

DS-C9132T-8PMESK9 is a Cisco MDS 9132T 32G Fibre Channel SAN switch bundle for compact storage-network access and rack-level SAN fabric growth. This order line provides 8 active Fibre Channel ports, includes eight Cisco 16G shortwave optics, uses the MDS 9132T 32-port switch platform, and ships with 2 fan modules, 1 power supply, and port-side exhaust airflow for cabinets built around back-to-front cooling.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	DS-C9132T-8PMESK9	Product compatibility	Cisco MDS 9000 Family
Product type	32G Fibre Channel SAN switch	Order configuration	Switch with 8 active ports, 8 x 16G SW optics, 2 fan modules, 1 power supply, and port-side exhaust airflow
Form factor	1RU fixed-switch form factor	Fibre Channel ports	16 SFP+ ports plus one 16-port SFP+ expansion slot
Active ports at order	8 active Fibre Channel ports	Maximum Fibre Channel ports	Up to 32 active Fibre Channel ports with expansion module and activation licenses
Fibre Channel speed support	4, 8, 16, and 32 Gbps autosensing	Dedicated bandwidth per port	32 Gbps
Aggregate bandwidth	1024 Gbps full duplex	Port activation license	8-port On-Demand Activation license for additional active ports
Expansion module option	16-port expansion module for MDS 9132T port expansion planning	Optional network license	MDS 9100 Enterprise package can be added separately when advanced MDS functions are required
Buffer credits	Up to 8300 buffer credits for a group of 16 ports	Default buffer credits per port	500 buffer credits per port
Maximum buffer credits for a single port	8270 buffer credits in the port group	Port channel support	Up to 16 load-balanced physical links in one port channel
Fibre Channel port types	E, F, and B standard port types; SD, ST, NP, and TE enhanced port types	NVMe/FC support	NVMe/FC listed by Cisco for the platform
Management Ethernet ports	Two out-of-band 10/100/1000 Ethernet management ports	Console port	RS-232 serial console port
USB port	USB power-on auto-provision port	Network management	Cisco Data Center Network Manager and standards-based SNMP management listed
Minimum NX-OS release	Cisco MDS NX-OS Release 8.2(1) or later	Minimum Cisco DCNM release	Cisco DCNM Release 10.4(1) or later
Fan modules	2 fan modules in the ordering description	Power supplies	1 power supply in the ordering description
Default power supply	DS-CAC-650W-E 650W AC port-side exhaust power supply; two supplies in the order configuration	AC input voltage	100 to 240 VAC

AC input frequency	50 to 60 Hz nominal	Power supply output capacity	650W
Power supply output voltage	12V +/- 5 percent, up to 54A	Output hold-up time	20 ms
Maximum system power	180W	Heat dissipation	614 BTU/hr
Typical power consumption	100W at 110V/60Hz and 98W at 220V/50Hz with 16 x 32G optics, 50 percent traffic, 1 PSU, and 2 fan modules	Airflow direction	Back to front toward ports using port-side exhaust fans
System airflow rate	50 CFM through system fan assembly at 77F (25C)	Maximum airflow rate	100 CFM maximum
Dimensions	1.72 x 17.3 x 20.11 in. (4.36 x 43.94 x 51.07 cm) excluding PSU and fan module handles	Form factor	1 RU
Weight	21.65 lb (9.82 kg)	Operating temperature	32 to 104F (0 to 40C)
Nonoperating temperature	-40 to 158F (-40 to 70C)	Operating relative humidity	10 to 90 percent noncondensing
Nonoperating relative humidity	10 to 95 percent noncondensing	Operating altitude	-197 to 6500 ft (-60 to 2000 m)
Included FC optics	8 x Cisco 16G Fibre Channel shortwave optics	16G SW transceiver product ID	DS-SFP-FC16G-SW
16G SW connector	Dual LC connectors	16G SW wavelength	850 nm
16G SW fiber type	Multimode fiber	16G SW cable distance	49 ft (15 m) on OM1, 115 ft (35 m) on OM2, 328 ft (100 m) on OM3, and 410 ft (125 m) on OM4 or OM5
Supported FC optics	32G SW, 32G LW, 16G SW, 16G LW, 8G SW, and 8G LW optics		

Get Price and Availability for DS-C9132T-8PMESK9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)[View Product Page](#)

Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.