

CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-8PMETK9

8x32G FC Ports · 8x32G SW Optics · Exhaust SAN Switch

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	DS-C9132T-8PMETK9
Category	MDS 9100 Series Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-8PMETK9

8x32G FC Ports · 8x32G SW Optics · Exhaust SAN Switch

The DS-C9132T-8PMETK9 is a Cisco MDS 9132T 32-Gbps Fibre Channel fixed SAN switch for connecting server racks to a SAN core with port-side exhaust airflow. The switch has 8 active ports, eight 32G shortwave optics, two fan modules and one power supply, and its ports autosense 4, 8, 16 or 32 Gbps within 1024 Gbps of full-duplex bandwidth.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	DS-C9132T-8PMETK9	Product compatibility	Cisco MDS 9000 Family
Product type	32G Fibre Channel SAN switching	Order configuration	8 active ports, 8 x 32G SW optics, 2 fan modules, 1 power supply, and port-side exhaust airflow
Form factor	1RU fixed-switch form factor	Fibre Channel ports	16 ports
Expansion module option	One 16-port SFP+ expansion slot	Maximum Fibre Channel ports	32 active Fibre Channel ports
Fibre Channel speed support	4, 8, 16, and 32 Gbps autosensing	Dedicated bandwidth per port	32 Gbps
Aggregate bandwidth	1,024 Gbps full duplex	Port activation license	M9132T-PL8= 8-port On-Demand Activation license
Expansion module option	M9XT-FC1632= 16-port SFP+ expansion module	Optional network license	M9100-ENT1K9= MDS 9100 switch Enterprise package
Minimum NX-OS release	Cisco MDS NX-OS Release 8.2(1) or later	Minimum Cisco DCNM release	Cisco DCNM Release 10.4(1) or later
Fan modules	2 fan modules	Power supplies	1 power supply
Default power supply	650W AC port-side exhaust power supply (spare PID DS-CAC-650W-E=); one supply in the order configuration	AC input voltage	100 to 240 VAC, 50 to 60 Hz nominal
Maximum power consumption	180W	Heat dissipation	614 BTU/hr
Airflow rate	50 CFM through system fan assembly at 77 F (25 C)	Dimensions	1.72 x 17.3 x 20.11 in. (4.36 x 43.94 x 51.07 cm) excluding PSU and fan module handles
Weight	9.82 kg (21.65 lb)	Operating temperature	32 to 104 F (0 to 40 C)
32G SW transceiver product ID	DS-SFP-FC32G-SW	32G SW media	850 nm multimode fiber
32G SW connector	Dual LC connectors	32G SW cable distance	65 ft (20 m) on OM2, 230 ft (70 m) on OM3, and 328 ft (100 m) on OM4 or OM5
Supported FC optics	32G SW, 32G LW, 16G SW, 16G LW, 8G SW, and 8G LW optics		

Get Price and Availability for DS-C9132T-8PMETK9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH