

CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-8PMITK9

8x32G FC Ports · 8x32G SW Optics · Intake SAN Switch

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	DS-C9132T-8PMITK9
Category	MDS 9100 Series Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · MDS 9100 SERIES SWITCHES

DS-C9132T-8PMITK9

8x32G FC Ports · 8x32G SW Optics · Intake SAN Switch

DS-C9132T-8PMITK9 is a Cisco MDS 9132T 32-Gbps Fibre Channel fixed SAN switch bundle for port-side-intake storage-networking racks.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	DS-C9132T-8PMITK9	Product compatibility	Cisco MDS 9000 Family
Product type	32G Fibre Channel SAN switch	Order configuration	8 active ports, 8 x 32G SW optics, 2 fan modules, 1 power supply, and port-side intake airflow
Form factor	1RU fixed-switch chassis	Fibre Channel ports	16 SFP+ Fibre Channel ports
Expansion module option	One 16-port SFP+ expansion slot	Active ports at order	8 active Fibre Channel ports
Maximum Fibre Channel ports	32 active Fibre Channel ports	Fibre Channel speed support	4, 8, 16, and 32 Gbps
Dedicated bandwidth per port	32 Gbps	Aggregate bandwidth	1024 Gbps full duplex
Port channel support	Up to 16 physical links in one port channel	Buffer credits	Up to 8300 buffer credits
Default buffer credits per port	500 buffer credits per port	Maximum buffer credits for a single port	8270 buffer credits within the port group
Port activation license	M9132T-PL8 8-port On-Demand Activation license	Expansion module option	M9XT-FC1632 16-port SFP+ expansion module
Optional network license	Cisco MDS 9000 Family Enterprise Package, purchased separately when required	Management Ethernet ports	Two out-of-band 10/100/1000 Mbps Ethernet management ports
Console and USB ports	RS-232 serial console port and USB power-on auto-provision port	Minimum NX-OS release	Cisco MDS NX-OS Release 8.2(1) or later
Minimum Cisco DCNM release	Cisco DCNM Release 10.4(1) or later	Fan modules	2 fan modules
Power supplies	1 power supply	Default power supply	DS-CAC-650W-I 650W AC port-side intake power supply; two supplies in the order configuration
AC input voltage	100 to 240 VAC	AC input frequency	50 to 60 Hz nominal
Typical power consumption	80W with 8 ports activated, 32G SFPs, traffic, and 25C ambient temperature	Airflow direction	Front to back, inward from ports, using port-side intake fans
System airflow rate	50 CFM through system fan assembly at 25C	Maximum airflow rate	100 CFM maximum
Dimensions	1.72 x 17.3 x 20.11 in. excluding PSU and fan module handles	Form factor	1 RU
Weight	21.65 lb (9.82 kg)	Operating temperature	32 to 104F (0 to 40C)

Nonoperating temperature	-40 to 158F (-40 to 70C)	Operating relative humidity	10 to 90 percent noncondensing
Nonoperating relative humidity	10 to 95 percent noncondensing	Operating altitude	-197 to 6500 ft (-60 to 2000 m)
32G SW transceiver product ID	DS-SFP-FC32G-SW	32G SW connector and media	32G Fibre Channel shortwave SFP+ using 850 nm multimode fiber
32G SW cable distance	65 ft (20 m) on OM2, 230 ft (70 m) on OM3, and 328 ft (100 m) on OM4 or OM5	Supported FC optics	32G SW, 32G LW, 16G SW, 16G LW, 16G ELW, 8G SW, 8G LW, 8G ER, and 8G CWDM SFP+ optics

Get Price and Availability for DS-C9132T-8PMITK9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](tel:+8617181189993) WeChat [layer23-switch](https://www.layer23-switch.com) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.