

CISCO FIREPOWER 2100 SERIES

FPR2120-ASA-K9

6G ASA Firewall · 12xRJ45 4x1G SFP · 1RU 2120

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR2120-ASA-K9
Category	Cisco Firepower 2100 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 2100 SERIES

FPR2120-ASA-K9

6G ASA Firewall · 12xRJ45 4x1G SFP · 1RU 2120

FPR2120-ASA-K9 is a Cisco Firepower 2120 ASA firewall appliance in the Firepower 2100 Series for ASA-based firewall edge, VPN, and security-services deployments. It is a 1RU rack-mount platform with twelve RJ-45 10M/100M/1GBASE-T data ports, four fixed 1G SFP ports, a dedicated RJ-45 management interface, and no network module bay.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	FPR2120-ASA-K9	Product Type	Cisco Firepower 2120 ASA firewall appliance
Firewall Model	Firepower 2120	Security Software Role	Cisco ASA software
Form Factor	1RU rack mount	Chassis Dimensions	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Fixed RJ-45 Ports	12 x 10M/100M/1GBASE-T	Fixed SFP Ports	4 x 1G SFP
Maximum Ethernet Interfaces	16 total Ethernet ports	Network Module Bay	No network module bay
Management Port	1 x 10M/100M/1GBASE-T RJ-45	Console Port	1 x RJ-45 console
USB Port	1 x USB 2.0 Type-A	Airflow	Cold aisle to hot aisle through the I/O side
Storage	1 x 100 GB SSD installed; second slot reserved for MSP	Power Supply	Single integrated 250W AC power supply
Power Redundancy	No redundant PSU option on 2120	System Power	100/240V AC 1.9 A at 100 VAC
AC Frequency	50 to 60 Hz	Fan Design	Fixed fan design; not field-replaceable
Rack Mounting	2-post fixed brackets included; 4-post slide rails optional	Weight	16.1 lb (7.3 kg)
Operating Temperature	32 to 104F (0 to 40C)	Operating Humidity	10 to 85% noncondensing
Operating Altitude	10000 ft maximum	Stateful Inspection Firewall Throughput	6 Gbps
Multiprotocol Firewall Throughput	3 Gbps	Concurrent Firewall Connections	1.5 million
New Connections Per Second	28000	IPsec VPN Throughput	700 Mbps
Maximum VPN Peers	3500	Security Contexts	2 included; 25 maximum
High Availability	Active/active and active/standby	Local ASA Management	Adaptive Security Device Manager
Centralized ASA Management	Cisco Security Manager or Cisco Defense Orchestrator	ASA Essentials License PID	L-FPR2100-ASA=
Context License Options	L-FPR2K-ASASC-5= and L-FPR2K-ASASC-10=	Fixed SFP Release Baseline	Threat Defense 6.2 / ASA 9.12

Supported Fixed 1G SFPs	GLC-TE, GLC-SX-MMD, GLC-LH-SMD, GLC-EX-SMD, GLC-ZX-SMD		
-------------------------	--	--	--

Get Price and Availability for FPR2120-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.