

CISCO FIREPOWER 2100 SERIES

FPR2120-NGFW-K9

3.4G NGFW Firewall · 12x1G RJ45 4x1G SFP · Threat Defense

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR2120-NGFW-K9
Category	Cisco Firepower 2100 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 2100 SERIES

FPR2120-NGFW-K9

3.4G NGFW Firewall · 12x1G RJ45 4x1G SFP · Threat Defense

FPR2120-NGFW-K9 is a Cisco Firepower 2120 NGFW firewall appliance in the Cisco Firepower 2100 Series for network-edge threat defense, ordered as a 1RU Cisco Firepower Threat Defense platform with twelve RJ-45 Gigabit data ports, four fixed 1G SFP ports, no network module bay, a single integrated 250W AC power supply, and Cisco-confirmed 3.4 Gbps NGFW throughput.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	FPR2120-NGFW-K9	Product Type	Cisco Firepower 2120 NGFW firewall appliance
Firewall Model	Firepower 2120	Security Software Role	Cisco Firepower Threat Defense / NGFW
Form Factor	1RU rack mount	Dimensions	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Fixed RJ-45 Ports	12 x 10M/100M/1GBASE-T	Fixed SFP Ports	4 x 1G SFP
Maximum Ethernet Interfaces	16 total Ethernet ports	Network Module Bay	No network module bay
Management Port	1 x 10M/100M/1GBASE-T RJ-45	Console Port	1 x RJ-45 console
USB Port	1 x USB 2.0 Type-A	Storage	1 x 100 GB SSD installed; second slot reserved for MSP
Power Supply	Single integrated 250W AC power supply	Power Redundancy	No redundant PSU option on 2120
System Power	100/240V AC 1.9 A at 100 VAC	AC Maximum Input Current	Less than 2.7A at 100V
AC Frequency	50 to 60 Hz	Fan Design	Fixed fans; not field-replaceable
Rack Mounting	2-post fixed brackets included; 4-post mount rails optional	Weight	16.1 lb (7.3 kg) with 2 SSDs
Operating Temperature	32 to 104F (0 to 40C)	Operating Humidity	10 to 85% noncondensing
Operating Altitude	10000 ft maximum	Firewall Throughput	6 Gbps
NGFW Throughput	3.4 Gbps	FW + AVC Throughput	3.4 Gbps
FW + AVC + IPS Throughput	3.4 Gbps	IPS Throughput	3.5 Gbps
TLS Throughput	475 Mbps	Concurrent Sessions with AVC	1.5 million
New Connections with AVC	18000 per second	IPsec VPN Throughput	1.2 Gbps
Maximum VPN Peers	3500	Local Management	Cisco Firepower Device Manager supported

Centralized Management	Firewall Management Center or Cisco Defense Orchestrator	High Availability	Active/standby
Smart Licensing	Base license included automatically; optional feature licenses managed through Smart Software Licensing	TMC License PID	L-FPR2120T-TMC=
TMC Term Options	L-FPR2120T-TMC-1Y, L-FPR2120T-TMC-3Y, L-FPR2120T-TMC-5Y	Fixed SFP Release Baseline	Threat Defense 6.2 / ASA 9.12
Supported Fixed 1G SFPs	GLC-TE, GLC-SX-MMD, GLC-LH-SMD, GLC-EX-SMD, GLC-ZX-SMD		

Get Price and Availability for FPR2120-NGFW-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.