

CISCO FIREPOWER 2100 SERIES

FPR2140-ASA-K9

20G ASA Firewall · 12xRJ45 4xSFP+ · Dual AC 2140

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR2140-ASA-K9
Category	Cisco Firepower 2100 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 2100 SERIES

FPR2140-ASA-K9

20G ASA Firewall · 12xRJ45 4xSFP+ · Dual AC 2140

FPR2140-ASA-K9 is a Cisco Firepower 2140 ASA firewall appliance for Firepower 2100 Series deployments that run Cisco ASA software at branch, internet-edge, or data-center security boundaries.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR2140-ASA-K9	Product Type	Cisco Firepower 2140 ASA firewall appliance
Firewall Model	Firepower 2140	Security Software Role	Cisco ASA software
Form Factor	1RU rack mount	Chassis Dimensions	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Fixed RJ-45 Ports	12 x 10M/100M/1GBASE-T	Fixed SFP+ Ports	4 x 1/10G SFP+
Maximum Ethernet Interfaces	Up to 24 total Ethernet ports with network module	Network Module Bay	One network module slot
Network Module Options	8-port 1G SFP, 8-port 10G SFP+, and 1G or 10G fail-to-wire options	Management Port	1 x 10M/100M/1GBASE-T RJ-45
Console Port	1 x RJ-45 console	USB Port	1 x USB 2.0 Type-A
Airflow	Front to rear; cold aisle to I/O side	Storage	1 x 200 GB SSD installed; second slot reserved for MSP
Power Supply Included	Dual 400W AC power supplies	Power Supply Options	Single or dual 350W DC optional
Power Redundancy	1+1 AC or DC with dual supplies	AC Input Voltage	100 to 240V AC
AC Maximum Input Current	Less than 6A at 100V	AC Maximum Output Power	400W
AC Frequency	50 to 60 Hz	DC Input Voltage	-48V to -60VDC
DC Maximum Output Power	350W	Fan Design	1 hot-swappable fan tray with 4 fans
Fan Redundancy	3+1 redundant fan operation	Rack Mounting	4-post EIA-310-D rack rails included; optional 2-post brackets
Weight	21 lb (9.53 kg) with 2 power supplies, 1 network module, 1 fan module, and 2 SSDs	Operating Temperature	32 to 104F (0 to 40C)
Operating Humidity	10 to 85% noncondensing	Operating Altitude	10000 ft maximum
Noise	56 dBA at 25C; 77 dBA at highest system performance	Stateful Inspection Firewall Throughput	20 Gbps
Multiprotocol Firewall Throughput	10 Gbps	Concurrent Firewall Connections	3 million
New Connections Per Second	75000	IPsec VPN Throughput	2 Gbps

Maximum VPN Peers	10000	Security Contexts	2 included; 40 maximum
High Availability	Active/active and active/standby	Local ASA Management	Adaptive Security Device Manager
Centralized ASA Management	Cisco Security Manager or Cisco Defense Orchestrator	ASA Essentials License PID	L-FPR2100-ASA=
Context License Options	L-FPR2K-ASASC-5= and L-FPR2K-ASASC-10=	Strong Encryption PID	L-FPR2K-ENC-K9=
Network Module ASA Compatibility	FPR2K-NM-8X10G from ASA 9.9 or 9.8(2)/(3); FPR2K-NM-8X1G and fail-to-wire modules from ASA 9.10		

Get Price and Availability for FPR2140-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00253333333333333333) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.