

CISCO FIREPOWER 3100 SERIES

FPR3105-ASA-K9

10G ASA Firewall · 8xRJ45 8x1/10G SFP · 1RU 3105

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR3105-ASA-K9
Category	Cisco Firepower 3100 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 3100 SERIES

FPR3105-ASA-K9

10G ASA Firewall · 8xRJ45 8x1/10G SFP · 1RU 3105

The FPR3105-ASA-K9 is a Cisco Secure Firewall 3105 ASA appliance for branch and internet-edge perimeters that run Cisco Secure ASA software. The 1RU firewall is rated at 10.0 Gbps of stateful inspection throughput on 1500B UDP, 1.5 million concurrent connections and 2,000 VPN peers, with 8 RJ-45 ports, 8 1/10G SFP ports and one network module slot.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR3105-ASA-K9	Product type	Cisco Secure Firewall 3105 ASA appliance
Fixed RJ-45 ports	8 x 10M/100M/1GBASE-T Ethernet interfaces	Fixed SFP ports	8 x 1/10 Gigabit Ethernet SFP interfaces
Maximum Ethernet ports	Up to 24 total Ethernet ports with network module	Network module slot	One removable network module slot
3105 optional interface profile	10G SFP+ options	Multiprotocol firewall throughput	9 Gbps
IPsec VPN throughput	5.5 Gbps	SSD storage	1 x 900 GB SSD with 1 spare slot
Firewall model	Secure Firewall 3105	New connections per second	150000
Security contexts	2 included; 100 maximum	Clustering	No clustering on 3105
Sound pressure	65 dBA typical; 74 dBA maximum	Maximum VPN peers	2000
Stateful inspection firewall throughput	10 Gbps	High availability	Active/active and active/standby
Management port	1 x 1/10G SFP management port	Console port	1 x RJ-45 serial console
USB port	1 x USB Type-A port	ASA centralized management	Cisco Security Manager or Cisco Defense Orchestrator
Local management	Adaptive Security Device Manager	Security software role	Cisco Secure ASA
Minimum ASA release	ASA 9.19 and later	Power supply configuration	Single 400W AC; dual 400W AC optional; DC optional
Power redundancy	Available when an extra power supply is ordered	Power redundancy rule	Order an extra power supply for redundancy
AC input voltage	100 to 240V AC	DC input voltage	-48V to -60VDC
Concurrent firewall connections	1.5 million	AC maximum output power	400W
DC maximum output power	400W	Fan modules	2 hot-swappable dual fan modules
Airflow	Front to rear; I/O side to non-I/O side	Rack units	1RU
Dimensions	1.75 x 17 x 20 in. (4.4 x 43.3 x 50.8 cm)	Mounting	Standard 19-inch square-hole rack

Operating temperature	32 to 104F (0 to 40C)		
-----------------------	-----------------------	--	--

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM

Get Price and Availability for FPR3105-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3070123456789) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.