

CISCO · FIREWALLS

FPR3120-ASA-K9

22G ASA Firewall · 8xRJ45 8x1/10G SFP · 1RU 3120

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR3120-ASA-K9
Category	Firewalls
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · FIREWALLS

FPR3120-ASA-K9

22G ASA Firewall · 8xRJ45 8x1/10G SFP · 1RU 3120

The FPR3120-ASA-K9 is a Cisco Secure Firewall 3120 ASA appliance for edge firewall and VPN deployments that run Cisco Secure ASA software. The 1RU firewall provides 22.0 Gbps of stateful inspection throughput on 1500B UDP, 4 million concurrent connections, 10 Gbps of IPsec VPN throughput on a 450B UDP L2L test and 7,000 VPN peers across 8 RJ-45 and 8 1/10G SFP ports.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR3120-ASA-K9	Product type	Cisco Secure Firewall 3120 ASA appliance
ASA compatibility reference	ASA and ASDM compatibility listed per Secure Firewall 3120 model	Fixed RJ-45 ports	8 x 10M/100M/1GBASE-T Ethernet interfaces
Fixed SFP ports	8 x 1/10 Gigabit Ethernet SFP interfaces	Maximum Ethernet ports	Up to 24 total Ethernet ports with network module
Network module slot	One removable network module slot	3120 module options	8 x 1/10G network module options
Multiprotocol firewall throughput	17 Gbps	IPsec VPN throughput	10 Gbps
SSD storage	1 x 900 GB SSD with 1 spare slot	Firewall model	Secure Firewall 3120
New connections per second	500000	Projected IPsec VPN with offload	15.4 Gbps with ASA 9.18
Security contexts	2 included; 100 maximum	Clustering	8 chassis
ASA introduction	ASA 9.17(1) introduced ASA for Secure Firewall 3110 3120 3130 and 3140	Sound pressure	65 dBA typical; 74 dBA maximum
Maximum VPN peers	7000	Stateful inspection firewall throughput	22 Gbps
High availability	Active/active and active/standby	Management port	1 x 1/10G SFP management port
Console port	1 x RJ-45 console	USB port	1 x USB 3.0 Type-A port
ASA centralized management	Cisco Security Manager or Cisco Defense Orchestrator	Local management	Adaptive Security Device Manager
Security software role	Cisco Secure ASA	Power supply configuration	Single 400W AC; dual 400W AC optional; DC optional
Power redundancy	1+1 AC or DC with dual supplies	AC input voltage	100 to 240V AC
DC input voltage	-48V to -60VDC	Concurrent firewall connections	4 million
AC maximum output power	400W	DC maximum output power	400W
Fan modules	2 hot-swappable fan modules with 2 fans each	Rack units	1RU

Dimensions	1.75 x 17 x 20 in. (4.4 x 43.3 x 50.8 cm)	Operating temperature	32 to 104F (0 to 40C); designed to be NEBS ready, with certification pending
Operating humidity	10 to 85% noncondensing	Operating altitude	10000 ft maximum; the NEBS-ready operating profile extends to 13000 ft

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM

Get Price and Availability for FPR3120-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a96909090909090) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.