

CISCO FIREPOWER 3100 SERIES

FPR3130-ASA-K9

42G ASA · 8x25G SFP28 + 8xRJ45 · 1RU 3130 ASA Firewall

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR3130-ASA-K9
Category	Cisco Firepower 3100 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 3100 SERIES

FPR3130-ASA-K9

42G ASA · 8x25G SFP28 + 8xRJ45 · 1RU 3130 ASA Firewall

The FPR3130-ASA-K9 is a Cisco Secure Firewall 3130 ASA appliance in the Secure Firewall 3100 Series for internet edge and data center firewalls that run Cisco Secure ASA software. The appliance delivers 42 Gbps of stateful inspection throughput on 1500B UDP traffic and 14 Gbps of IPsec VPN with up to 15,000 peers, from eight RJ-45 ports, eight 1/10/25G SFP ports and one network module slot.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR3130-ASA-K9	Product type	Cisco Secure Firewall 3130 ASA appliance
ASA compatibility reference	ASA and ASDM compatibility listed per Secure Firewall 3130 model	Fixed RJ-45 ports	8 x 10M/100M/1GBASE-T Ethernet interfaces
Fixed SFP ports	8 x 1/10/25 Gigabit Ethernet SFP interfaces	Maximum Ethernet ports	Up to 24 total Ethernet ports with network module
Network module slot	One removable network module slot named NM-2	3130 / 3140 module options	8 x 1/10/25G, 4 x 40G, and 2 x 100G options
Fixed port first supported release	Threat Defense 7.1 / ASA 9.17 for 3110 3120 3130 and 3140	Multiprotocol firewall throughput	39 Gbps
IPsec VPN throughput	14 Gbps	SSD storage	1 x 900 GB SSD with 1 spare slot
Firewall model	Secure Firewall 3130	New connections per second	875000
Projected IPsec VPN with offload	28 Gbps with ASA 9.18	Security contexts	2 included; 100 maximum
Clustering	8 chassis	Sound pressure	65 dBA typical; 74 dBA maximum
Maximum VPN peers	15000	Stateful inspection firewall throughput	42 Gbps
High availability	Active/active and active/standby	Management port	1 x 1/10G SFP management port
Console port	1 x RJ-45 serial console	USB port	1 x USB 3.0 Type-A port
ASA centralized management	Cisco Security Manager or Cisco Defense Orchestrator	Local management	Adaptive Security Device Manager
Security software role	Cisco Secure ASA	Power supply configuration	Dual 400W AC; single or dual 400W DC optional
Power redundancy	1+1 AC or DC with dual supplies	AC input voltage	100 to 240V AC
DC input voltage	-48V to -60VDC	Concurrent firewall connections	6 million
AC maximum output power	400W	DC maximum output power	400W
Fan modules	2 hot-swappable dual fan modules	Airflow	Front to rear; I/O side to non-I/O side

Rack units	1RU	Dimensions	1.75 x 17 x 20 in. (4.4 x 43.3 x 50.8 cm)
Operating temperature	32 to 104F (0 to 40C)	Operating humidity	10 to 85% noncondensing
Operating altitude	10000 ft maximum		

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-25G-SR-S	25GBASE-SR SFP28 - 850nm MMF - 100m OM4
Optics	SFP-10/25G-CSR-S	10/25GBASE-CSR SFP28 - 850nm MMF - 300 m OM3 / 400 m OM4 -
Optics	SFP-10/25G-LR-S	10/25GBASE-LR SFP28 - 10 km G.652 SMF - 0 to 70°C Commercial Temperature
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM

Get Price and Availability for FPR3130-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)
[View Product Page](#)


Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.