

CISCO FIREPOWER 4200 SERIES

FPR4112-ASA-K9

40G ASA Firewall · 8x10G SFP+ · 2 NM Bays

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4112-ASA-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4112-ASA-K9

40G ASA Firewall · 8x10G SFP+ · 2 NM Bays

The FPR4112-ASA-K9 is a Cisco Secure Firewall 4100 Series Firepower 4112 ASA appliance for internet-edge and data center perimeters. The 1RU appliance delivers 40 Gbps of stateful inspection throughput, 10 million concurrent connections and 9 Gbps of IPsec VPN, with eight fixed 1G/10G SFP+ ports and two network module bays.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	FPR4112-ASA-K9	Product type	Cisco Firepower 4112 ASA appliance
Firewall model	FPR-4112	Rack units	1RU
Dimensions	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)	On-chassis data ports	8 x 10 Gigabit Ethernet SFP+
Network module bays	2	Maximum interface expansion	Up to 4 x 100GE QSFP28, 24 x 10GE SFP+, 8 x 40GE QSFP+, or 24 x 1GE ports with network modules and fixed ports
Management port	1 Gigabit Ethernet SFP port	Serial port	1 x RJ-45 console
USB port	1 x USB 2.0	Storage	400 GB
Fan modules	6 hot-swappable fans	Power supply configuration	Single 1100W AC; dual optional; single or dual 950W DC optional
Power redundancy	1+1	AC input voltage	100 to 240V AC
AC maximum output power	1100W	DC input voltage	-40V to -60VDC
DC maximum output power	950W	Stateful inspection firewall throughput	40 Gbps
Multiprotocol firewall throughput	30 Gbps	Concurrent firewall connections	10 million
New connections per second	400000	Firewall latency	3.5 microseconds with UDP 64B test traffic
IPsec VPN throughput	9 Gbps	Maximum VPN peers	10000
Security contexts	10 included; 250 maximum	High availability	Active/active or active/standby
Clustering	Up to 16 appliances	Fixed port transceiver support	1G and 10G SFP/SFP+ options listed for Firepower 4112 fixed ports
Fixed port first supported release	Threat Defense 6.6 / ASA 9.14	Mounting	4-post EIA-310-D rack mount rails included
Weight	17.87 kg (39.4 lb) with 2 power supplies, 2 network modules, and 6 fans	Operating temperature	32 to 104F (0 to 40C)
Operating humidity	5 to 95% noncondensing	Operating altitude	10000 ft maximum

Noise	63 dBA typical; 74 dBA maximum		
-------	--------------------------------	--	--

Get Price and Availability for FPR4112-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.